

LPS3C12X220

Linear Power Supply/Charger

Altronix LPS3C12X220 is specifically designed to provide the power needed by the most demanding security and access control applications. It converts a 220VAC 50/60Hz input to a 12VDC, 2.5A output.



LPS3C12X220

Specifications

Input

Voltage 220VAC (working range 198VAC - 256VAC),
50/60Hz, 0.25A

Outputs

Voltage 12VDC
Current 2.5A continuous supply current
Other Short circuit and thermal overload protection
Filtered and regulated

Back-up Battery *(not included)*

Type Sealed lead acid or gel type
Failover Upon AC loss, instantaneous

Indicators (LED)

Input Input voltage is present
DC Output Powered

Physical and Environmental

Enclosure Dimensions (H x W xD)

15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)
Accommodates one (1) 12VDC/12AH battery

Product Weight 11.1 lb. (5.03 kg)

Shipping Weight 12.3 lb. (5.58 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr. (approx.): 15 BTU/Hr.

Lifetime Warranty