



401 CLEVIS HANGER



CERTIFICATIONS



FEATURES

Recommended for the suspension of stationary non-insulated pipe lines

Flared edges help prevent sharp surfaces from coming into contact with the pipe (1/2" to 2" pipe sizes)

Clevis bottom pivots to allow pipe to be fed from either direction


SPECIFICATIONS

Material: Steel

Catalog Number	Finish	Pipe Size	Outer Diameter(OD)	Rod Size(RS)	A	B	C	Static Load(F)	Certifications
4010050HD	Hot-Dip Galvanized	1/2"	0.840"	3/8"	2 1/8"	15/16"	1/4"	600 lb	cUL, UL
4010050EG	Electrogalvanized, Pregalvanized	1/2"	0.840"	3/8"	2 5/16"	1 1/8"	3/8"	600 lb	cUL, ITB, UL
4010075EG	Electrogalvanized, Pregalvanized	3/4"	1.050"	3/8"	2 1/2"	1 1/4"	3/8"	600 lb	cUL, FM, ITB, UL
4010075HD	Hot-Dip Galvanized	3/4"	1.050"	3/8"	2 3/8"	1 1/16"	3/8"	600 lb	cUL, FM, UL
4010100EG	Electrogalvanized, Pregalvanized	1"	1.315"	3/8"	2 13/16"	1 3/8"	3/8"	600 lb	cUL, FM, ITB, UL
4010100HD	Hot-Dip Galvanized	1"	1.315"	3/8"	2 13/16"	1 3/8"	9/16"	600 lb	cUL, FM, UL
4010125EG	Electrogalvanized, Pregalvanized	1 1/4"	1.660"	3/8"	3 1/8"	1 9/16"	3/8"	600 lb	cUL, FM, ITB, UL
4010125HD	Hot-Dip Galvanized	1 1/4"	1.660"	3/8"	3 5/16"	1 3/4"	11/16"	600 lb	cUL, FM, UL
4010150EG	Electrogalvanized, Pregalvanized	1 1/2"	1.900"	3/8"	3 11/16"	2 1/16"	11/16"	600 lb	cUL, FM, ITB, UL

Catalog Number	Finish	Pipe Size	Outer Diameter(OD)	Rod Size(RS)	A	B	C	Static Load(F)	Certifications
4010150HD	Hot-Dip Galvanized	1 1/2"	1.900"	3/8"	4"	2 1/4"	1 1/16"	600 lb	cUL, FM, UL
4010200EG	Electrogalvanized, Pregelvanized	2"	2 3/8"	3/8"	4 5/16"	2 1/2"	7/8"	600 lb	cUL, FM, ITB, UL
4010200HD	Hot-Dip Galvanized	2"	2 3/8"	3/8"	4 1/2"	2 9/16"	1 1/8"	600 lb	cUL, FM, UL
4010250EG	Electrogalvanized, Pregelvanized	2 1/2"	2 7/8"	1/2"	5 5/16"	3 1/16"	1"	1,130 lb	cUL, FM, ITB, UL
4010250HD	Hot-Dip Galvanized	2 1/2"	2 7/8"	1/2"	5 1/4"	2 13/16"	1 1/16"	1,130 lb	cUL, FM, UL
4010300EG	Electrogalvanized, Pregelvanized	3"	3 1/2"	1/2"	6 1/16"	3 1/2"	1 1/8"	1,130 lb	cUL, FM, ITB, UL
4010300HD	Hot-Dip Galvanized	3"	3 1/2"	1/2"	6"	3 1/4"	7/8"	1,130 lb	cUL, FM, UL
4010350EG	Electrogalvanized, Pregelvanized	3 1/2"	4"	1/2"	6 13/16"	4"	1 5/16"	1,130 lb	cUL, FM, UL
4010400EG	Electrogalvanized, Pregelvanized	4"	4 1/2"	5/8"	7 7/16"	4 3/8"	1 3/8"	1,130 lb	cUL, FM, ITB, UL
4010400HD	Hot-Dip Galvanized	4"	4 1/2"	5/8"	7 3/4"	4 1/4"	1 3/4"	1,130 lb	cUL, FM, UL
4010500EG	Electrogalvanized, Pregelvanized	5"	5 9/16"	5/8"	9 1/16"	5 1/8"	1 5/8"	1,430 lb	cUL, FM, ITB, UL
4010500HD	Hot-Dip Galvanized	5"	5 9/16"	5/8"	9 3/4"	5 11/16"	2 3/16"	1,430 lb	cUL, FM, UL
4010600EG	Electrogalvanized, Pregelvanized	6"	6 5/8"	3/4"	10 9/16"	6"	1 7/8"	1,940 lb	cUL, FM, ITB, UL
4010600HD	Hot-Dip Galvanized	6"	6 5/8"	3/4"	11 3/4"	6 7/8"	2 11/16"	1,940 lb	cUL, FM, UL
4010800EG	Electrogalvanized, Pregelvanized	8"	8 5/8"	3/4"	14"	8"	3 1/8"	2,000 lb	cUL, FM, ITB, UL
4010800HD	Hot-Dip Galvanized	8"	8 5/8"	3/4"	14"	8 1/8"	3 1/8"	2,000 lb	cUL, FM, UL
4011000EG	Electrogalvanized, Pregelvanized	10"	10 3/4"	7/8"	16 1/2"	9"	2 9/16"	3,600 lb	ITB
4011000HD	Hot-Dip Galvanized	10"	10 3/4"	7/8"	16 1/2"	9 1/16"	2 9/16"	3,600 lb	
4011200EG	Electrogalvanized, Pregelvanized	12"	12 3/4"	7/8"	18 5/8"	10 3/16"	3 1/16"	3,800 lb	ITB
4011200HD	Hot-Dip Galvanized	12"	12 3/4"	7/8"	18 5/8"	10 3/16"	3 1/16"	3,800 lb	
4011400EG	Electrogalvanized, Pregelvanized	14"	14"	1"	21 3/4"	12 1/8"	4 3/8"	4,200 lb	ITB
4011600EG	Electrogalvanized, Pregelvanized	16"	16"	1"	24"	13 1/2"	4 5/8"	4,600 lb	ITB
4011800EG	Electrogalvanized, Pregelvanized	18"	18"	1 1/8"	26 3/4"	15"	5 1/8"	4,800 lb	ITB
4012000EG	Electrogalvanized, Pregelvanized	20"	20"	1 1/4"	30"	17"	6"	4,800 lb	ITB
4012400EG	Electrogalvanized, Pregelvanized	24"	24"	1 1/4"	34 1/8"	18 5/8"	5 11/16"	4,800 lb	ITB

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER