



HAMMER-ON FLANGE CLIP, SIDE MOUNT



CERTIFICATIONS



FEATURES

Provides an attachment for wire, S-hooks, chain, nVent CADDY Speed Link or other assemblies to flanges and profiles

Fits most beams


Installs with just a hammer

SPECIFICATIONS

Finish: nVent CADDY Armour

Catalog Number	Material	Flange Thickness(FT)	Hole Size(HS)	Static Load(F)	Packing Quantity	Certifications
2H4	Spring Steel	3/32" - 9/64"	1/4"	160 lb	1.0000	cUL, ITB, UL
4H24	Spring Steel	1/8" - 1/4"	1/4"	200 lb	1.0000	cUL, ITB, UL, CE, 4H, EM, EBC
4H24SS	Stainless Steel 301 (EN 1.4310)	1/8" - 1/4"	1/4"	140 lb	1.0000	
4H1318	Spring Steel	13/16" - 1 1/8"	1/4"	200 lb	1.0000	cUL, UL
4H58	Spring Steel	5/16" - 1/2"	1/4"	200 lb	1.0000	cUL, ITB, UL, CE, 4H, EM, EBC
4H58SS	Stainless Steel 301 (EN 1.4310)	5/16" - 1/2"	1/4"	140 lb	1.0000	
4H912	Spring Steel	9/16" - 3/4"	1/4"	200 lb	1.0000	cUL, ITB, UL, CE, 4H, EM, EBC
4H912SS	Stainless Steel 301 (EN 1.4310)	9/16" - 3/4"	1/4"	140 lb	1.0000	

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF**
TRACER