



512 NVENT CADDY EZ RISER FOR CLOSE QUARTERS



CERTIFICATIONS



FEATURES

Innovative design eliminates loose hardware, simplifying installation

Serrated flange-head bolts eliminate need for wrenches on both bolt and nut

Short ears allow for use in spaces where full-sized risers do not fit

Conforms with Federal Specification WW-H-171 (Type 8), Manufacturers Standardization Society (MSS) SP-58 (Type 8)

SPECIFICATIONS

Finish: Electrogalvanized

Material: Steel

Catalog Number	Pipe Size	Outer Diameter(OD)	Hole Size(HS)	A	B	Static Load(F)
5120100EG	1"	1.315"	7/16"	5"	1"	255 lb
5120125EG	1 1/4"	1.660"	7/16"	5 5/8"	1"	255 lb
5120150EG	1 1/2"	1.900"	7/16"	6 1/8"	1"	255 lb
5120200EG	2"	2 3/8"	7/16"	6 5/8"	1 3/16"	255 lb
5120250EG	2 1/2"	2 7/8"	7/16"	7 5/8"	1 3/16"	390 lb
5120300EG	3"	3 1/2"	9/16"	8 5/8"	1 3/16"	530 lb
5120400EG	4"	4 1/2"	9/16"	10 1/4"	1 1/2"	810 lb
5120600EG	6"	6 5/8"	9/16"	14 5/16"	2"	1,570 lb

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER