



NVENT CADDY EZ RISER



CERTIFICATIONS



FEATURES

One-piece hinge design comes out of the box ready to install

Lack of loose hardware eliminates dropped or lost components, eliminating potential rework and speeding up installation

Carriage bolts seat into clamp, eliminating the need for multiples tools when tightening

Installs up to 60% faster than standard riser clamps and 45% faster than the industry-leading first generation EZ Riser

Multi-functional clamp can be installed in several approved orientations, simplifying material handling

Integrated second set of bolt holes allow the assembly to easily adapt from a riser clamp into a stand-off support

In spaces where full-sized riser clamps do not fit, integrated score marks allow for easy removal of ears

Retains listing when the ears are removed for close quarters, uniquely making the nVent CADDY EZ Riser capable of a listing in both installations

Recommended for suspending vertical steel pipe risers

No need to stock and use separate part families for standard and close quarter clamps to offer a full range of listed parts, reducing inventory by 38%

Conforms with Federal Specification WW-H-171 (Type 8), Manufacturers Standardization Society (MSS) SP-58 (Type 8)

SPECIFICATIONS

Finish: Electrogalvanized

Material: Steel


Catalog Number	Pipe Size	Outer Diameter(OD)	Hole Size(HS)	A	B	C	Static Load(F)
EZR0050	1/2"	0.840"	0.390"	8 1/2"	5 1/8"	7/8"	255 lb
EZR0075	3/4"	1.050"	0.390"	9"	5 3/8"	7/8"	255 lb
EZR0100	1"	1.315"	0.390"	9"	5 5/8"	7/8"	255 lb
EZR0125	1 1/4"	1.660"	0.390"	9 1/2"	6"	7/8"	255 lb
EZR0150	1 1/2"	1.900"	0.390"	9 7/8"	6 1/4"	7/8"	255 lb
EZR0200	2"	2 3/8"	0.390"	10 1/4"	7"	1"	255 lb
EZR0250	2 1/2"	2 7/8"	0.390"	11"	7 1/2"	1"	390 lb
EZR0300	3"	3 1/2"	0.390"	11 3/4"	8 1/8"	1"	530 lb
EZR0350	3 1/2"	4"	0.520"	12 5/8"	9 3/8"	1 1/4"	670 lb
EZR0400	4"	4 1/2"	0.520"	13"	10"	1 1/4"	810 lb
EZR0500	5"	5.563"	0.520"	14 1/2"	11 3/4"	1 1/2"	1,160 lb
EZR0600	6"	6 5/8"	0.520"	16"	12 3/4"	1 1/2"	1,570 lb

ADDITIONAL PRODUCT DETAILS

Clamp is fitted for steel pipe and should be installed below a coupling or shear lug, with bolts torqued to recommended value.

Use of a socket or driver is recommended for installation.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER