

Class 125 (Standard)

Fig. 3351R Reducing 90° Elbow



For Listings/Approval Details and Limitations, visit our website at www.asc-es.com or contact an ASC Engineered Solutions™ Sales Representative.

Material Specifications

Dimensions: ASME B16.4 Class 125

Material: ASTM A126


Finish: Black or Hot Dip Galvanized per ASTM A153 Class A

Threads: NPT per ASME B1.20.1

Agency Approvals: All cast iron threaded fittings are UL/ULC Listed and FM Approved.

Figure 3351R Reducing 90° Elbow

Nominal Size	Maximum Working Pressure ▲	Dimensions		Approx Wt. Each
		A	B	
In. (mm)	psi (kPa)	In. (mm)	In. (mm)	Lbs. (kg)
1 x 1/2	300	1.26	1.36	0.64
25 x 15	2065	32.00	34.54	0.29
1 x 3/4	300	1.37	1.45	0.87
25 x 20	2065	34.79	36.83	0.39
1 1/4 x 1/2	300	1.34	1.53	0.96
32 x 15	2065	34.03	38.86	0.44
1 1/4 x 3/4	300	1.45	1.62	1.13
32 x 20	2065	36.83	41.14	0.51
1 1/4 x 1	300	1.58	1.67	1.16
32 x 25	2065	40.13	42.41	0.53
1 1/2 x 1/2	300	1.41	1.66	1.17
40 x 15	2065	35.81	42.16	0.53
1 1/2 x 3/4	300	1.52	1.75	1.28
40 x 20	2065	38.60	44.45	0.58
1 1/2 x 1	300	1.65	1.80	1.51
40 x 25	2065	41.91	45.72	0.68
1 1/2 x 1 1/4	300	1.82	1.88	1.62
40 x 32	2065	46.22	47.75	0.73
2 x 1/2	300	1.49	1.88	2.00
50 x 40	2065	37.84	47.75	0.91
2 x 3/4	300	1.60	1.97	2.05
50 x 20	2065	40.64	50.03	0.93
2 x 1	300	1.73	2.02	2.10
50 x 25	2065	43.94	51.30	0.95
2 x 1 1/4	300	1.90	2.10	2.30
50 x 32	2065	48.26	53.34	1.04
2 x 1 1/2	300	2.02	2.16	2.60
50 x 40	2065	51.30	54.86	1.18



▲ - Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit asc-es.com or contact your local ASC Engineering Solutions™ Representative.



PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	