

Cap
Fig. 3224



Material Specifications

Dimensions: ASME B16.3

Material: ASTM A536 Grade 65-45-12

Finish: Black


Threads: NPT per ASME B1.20.1

Agency Approvals: All ductile iron threaded fittings are UL/ULC Listed and FM Approved.

Note: Ductile iron fittings have higher tensile strength than that of steel pipe. Therefore, over tightening can cause damage to pipe threads which may cause leakage. Ductile iron fittings should be tightened approximately three turns beyond hand tight, but no more than four turns.

Figure 3224 Cap

Nominal Size	Maximum Working Pressure ▲	Dimension A	Approx Wt. Each
In. (mm)	psi (kPa)	In. (mm)	Lbs. (kg)
1	500	1.16	0.32
25	3450	29.46	0.15
1¼	500	1.28	0.43
32	3450	32.51	0.20
1½	500	1.33	0.60
40	3450	33.78	0.27
2	500	1.45	0.91
50	3450	36.83	0.41



▲ – Working Pressure Ratings are for reference only and based on Sch. 40 pipe. For the latest UL/ULC, and FM pressure ratings versus pipe schedule, please visit asc-es.com or contact your local ASC Engineered Solutions™ Representative.

PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	