

A SERIES

SPRINGWOUND AUTO OFF IN-WALL TIME SWITCH



Wallplate not included

APPLICATIONS



- Whole house fans
- Indoor/Outdoor lighting
- Bathroom fans and lights
- Self storage

FEATURES

VARIABLE TIMING: Twist knob for time ON setting. Time ON lengths from 15 minutes to 12 hour vary by model.

HOLD FEATURE: Some models have position for constant ON.


EASY SET: No adjustments. Just wire and go!

EASY WIRING: No neutral required. Great for retrofit! Use as single or in multi-gang box with no de-rating.

SWITCH TYPE: SPST.

COLOR: Ivory, Light Almond, White.

WALL PLATE: Fits standard or decorator style wall plates, see below (not included).



CONTACT RATINGS

TYPE	VOLTAGE	RATING
Resistive	125VAC	20A
	250VAC	10A
	277VAC	10A
Inductive	125VAC	20A
	250VAC	10A
	277VAC	10A
Tungsten	125VAC	7A
Motor	125VAC	1HP
	250VAC	2HP

SPECIFICATIONS

INPUT VOLTAGE:
125/250/277VAC, 50/60Hz.

TERMINAL SIZE: #12AWG.

OPERATING TEMPERATURE:
32°F to 122°F (0°C to 50°C).

ORDERING INFO

CATALOG NO.	UPC CODE	HOLD FEATURE	COLOR
15 MINUTE MAX.			
A515MH	15020	With Hold	Ivory
A515MHW	15120		White
A515M	15013	No Hold	Ivory
A515MW	15113		White
A515MA	15127		Light Almond
30 MINUTE MAX.			
A530MH	15021	With Hold	Ivory
A530MHW	15121		White
A530M	15014	No Hold	Ivory
A530MW	15114		White
A530MA	15128		Light Almond
60 MINUTE MAX.			
A560MH	15022	With Hold	Ivory
A560MHW	15122		White
A560M	15015	No Hold	Ivory
A560MW	15115		White
2 HOUR MAX.			
A502HHW	15123	With Hold	White
A502H	15016	No Hold	Ivory
A502HW	15116		White
6 HOUR MAX.			
A506HHW	15125	With Hold	White
A506H	15018	No Hold	Ivory
A506HW	15118		White
12 HOUR MAX.			
A512HH	15026	With Hold	Ivory
A512HHW	15126		White
A512H	15019	No Hold	Ivory
A512HW	15119		White

All A Series timers have SPST switch type.

CAUTION: This timer is not to be used in precision timing applications where inaccurate timing could have dangerous consequences (i.e. sun lamp, sauna, etc.).

C SERIES

COMMERCIAL STYLE

SRINGWOUND AUTO OFF

IN-WALL TIME SWITCH



Wallplate included

SPECIFICATIONS

INPUT VOLTAGE:

125/250/277VAC, 50/60Hz.

TERMINAL SIZE: #12AWG.

OPERATING TEMPERATURE:

32°F to 122°F (0°C to 50°C).

APPLICATIONS



- Ventilating fans
- HVAC
- Whirlpools
- Self storage
- Motors and pumps

FEATURES

VARIABLE TIMING: Twist knob for time ON setting. Time ON lengths from 15 minutes to 12 hour vary by model.

HOLD FEATURE: Some models have position for constant ON.

EASY SET: No adjustments. Just wire and go!

EASY WIRING: No neutral required. Great for retrofit!

SWITCH TYPE: SPST, except C460M and C412H – DPST

COLOR: Metal-brushed aluminum.

WALL PLATE: Includes real metal wall plate with screw mounting, to add extra security for commercial applications.

CONTACT RATINGS

TYPE	VOLTAGE	RATING
Resistive	125VAC	20A
	250VAC	10A
	277VAC	10A
Inductive	125VAC	20A
	250VAC	10A
	277VAC	10A
Tungsten	125VAC	7A
Motor	125VAC	1HP
	250VAC	2HP

ORDERING INFO

CATALOG NO.	UPC CODE	HOLD FEATURE
-------------	----------	--------------

15 MINUTE MAX.

C515M	15501	No Hold
-------	-------	---------

30 MINUTE MAX.

C530M	15503	No Hold
-------	-------	---------

60 MINUTE MAX.

C560M	15505	No Hold
-------	-------	---------

C560MH	15506	With Hold
--------	-------	-----------



C460M*	15011	No Hold
--------	-------	---------

2 HOUR MAX.

C502H	15507	No Hold
-------	-------	---------

6 HOUR MAX.

C506H	15511	No Hold
-------	-------	---------

12 HOUR MAX.

C512H	15513	No Hold
-------	-------	---------

C512HH	15514	With Hold
--------	-------	-----------



C412H*	15010	No Hold
--------	-------	---------

*DPST switch type.

CAUTION: This timer is not to be used in precision timing applications where inaccurate timing could have dangerous consequences (i.e. sun lamp, sauna, etc.).