

## Macurco **GD-2B** Combustible Gas Detector

1. 9 to 32 VDC Input or 12-24 VAC input
2. Buzzer Option - Removable jumper to select audible alarm or silent operation
3. Test Button - Activates alarm relay for system test
4. Security Series Housing - Sister product to the CM-E1 CO Detector
5. Low profile - Extends less than 3/8" from the wall when flush mounted
6. Single Gang Box - Flush mounts in a 2" x 4" single electrical box
7. End of life indication - Alerts when the gas detector needs replacing (10 years)
8. Latch in option - Removable jumper to select normal or latch in operation
9. Alarm Relay Option – Removable jumper to select NC or NO alarm relay operation
10. Speed Mount Installation - Snap-in wire harness for swift and easy installation



## Macurco **GD-2A** Combustible Gas Detector

1. 12-24 VDC or VAC input
2. No Buzzer, audible alarm only available at the alarm panel
3. No test button - must be tested with gas
4. Old style Macurco housing does not match Macurco CO detector
5. GD-2A units extend 7/8" from the wall when flush mounted
6. Flush mount in a 4" x 4" or 2-gang electrical box
7. No specific End of life indication, just simple trouble indicator
8. Latch in option - User clips a loop on the printed circuit board for latch in, non-reversible
9. Alarm Relay Option- User must rewire at the terminal block for NO or NC operation
10. User must wire at the terminal block

