Product Data Sheet



19" LCD Display

UL-LCD19

The Advanced UL-LCD19, is a UL864/ULC-S527 listed, high resolution, 19 inch LCD display that is fully compatible with the Advanced ULPC-RACK PC. The UL-LCD19 is a small, light, compact unit that can be ordered with or without touch screen option and may be supplied in an 8U rack mount option.

The ULPC-RACK PC is ideal for applications requiring PC based fire graphics annunciation and control, and is ideally suited for proprietary applications. The PCs come pre-loaded from the factory with the Advanced Ad-VIEW graphics package. Customization of graphic images and system wide controls is made simple with the Ad-VIEW package. Interface to an Axis^{AX} Series Intelligent Fire Alarm Control Panel and/or network is through an AX-BMS Module. All nodes on the network (up to 200) communicate status and system event information back through the AX-BMS Module to the PC. All communications circuitry is fault tolerant.





Unique Features:

- 19" LCD Display
- 1280 x 1024 Resolution
- 16.2 Million Colors
- Touch Screen Option
- 8U Rack Mount Option

Features:

- Thin Frame Bezel
- Small Footprint
- Black Frame and Stand
- (2) 2 Watt Speakers

Listings and Approvals:

- UL 864 Listed: file UOXX2.S7066
- ULC-S527 Listed

19" LCD Displays Specification Details

LCD Screen

Active Area 14.8" x 11.85" 376mm x 301mm

Resolution 1280 x 1024

Brightness (typical) 270 cd/m2

Viewing Angle Horizontal: 80L/80R (CR>5) Vertical: 80U/70D (CR>5) Colors 16.2 million

Contrast Ratio 700:1

Touchscreen (optional) Capacitive, USB/Serial

Physical

Dimensions w/stand (W x H x D)

VESA Mount Standard 100mm x 100mm Without Base 16.73" x 16.25" x 2.36" 425mm x 347mm x 60mm

With Touchscreen 16.73" x 15.75" x 8"

425mm x 400mm x 203.2mm

Without Touchscreen 16.73" x 16.3" x 9.44"

425mm x 414mm x 240mm

Weight 14.3 lbs. without touchscreen (Standard Base)

15.3 lbs. with touchscreen and base 15.5 lbs. with 8U Rackmount Bracket

Color Black

Electrical


Input Signal DVI-D

VGA 15 pin D-Sub Power Supply Input AC 120V @ 60Hz

Power Consumption (maximum) 30 Watts

Ordering Information

UL-LCD19 LCD, 19", 1280 x 1024, UL 864



Advanced Fire Systems Inc 100 South Street, Hopkinton, MA 01748

Tel: (508) 435-9995
Fax: (508) 435-9990
Email: usa@advancedco.com
Web: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.

900-062 Rev. 1.1 Page 2 of 2