

VertiLine563

Rack Mount Power Supply/Charger



Altronix Vertiline563 EIA 19" 1U rack mountable dual independent power supply with optional battery backup provides 56VDC. It is intended primarily to be used in conjunction with respective Altronix current and future products that require 56VDC input such as: eBridge4PCR, eBridge16PCR, and eBridge1PCR multi-port and single port IP/PoE over coax adapters. However, it can also be employed wherever 56VDC level power sources are needed.

There are applications which may require delivering power in a range of 48VDC to 57VDC over CAT5 cable for distances up to 100m. For these applications transmission at the higher voltage is more efficient, as it reduces cable losses when compared to the lower voltage.



VertiLine563

Specifications

Input

Voltage 115VAC, 60Hz, 4.9A

Output

Two PTC protected outputs

Voltage 56VDC

Current 3A max. each output

Other Short circuit and thermal overload protection
Filtered and regulated

Back-up Battery *(not included)*

Type Sealed lead acid or gel type

Failover Upon AC loss, instantaneous

Indicators (LED)

Two (2) individual AC LEDs

Agency Listings

UL/cUL UL60950-1
(Information Technology Equipment)

CE European Conformity

C-Tick compliant

Physical and Environmental

Dimensions (H x W x D)

Modular 1U standard EIA 19" rack mount chassis
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)

Product Weight 7 lb. (3.18 kg)

Shipping Weight 8.3 lb. (3.76 kg)

Temperature

Operating 0°C to 40°C (32°F to 104°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr. (approx.): 172 BTU/Hr.

Accessories *(order separately)*



RE2

RE2

Rack Mount Battery Enclosure accommodates up to four (4) 12VDC/7AH batteries

Lifetime Warranty