

# Trove1HW1R

Rack Access and Power Integration Solution for Honeywell



Altronix Trove1HW1R consists of a high-capacity rack enclosure with removable backplane. This unit easily combines Altronix power/accessories with various combinations of Honeywell ProWatch and WinPak boards in a streamlined package. Trove simplifies board layout and wire management, reducing installation time and labor costs.



THE POWER OF CONNECTED

Trove1HW1R

\* Boards are not included

## Trove1HW1R (Trove1R Enclosure + THW1R Backplane) and THW1R (Backplane) Features

- Accommodates the following Honeywell controllers with or without Altronix power/accessories:
  - Up to four (4) PRO32IC, PRO32R2, PRO32IN, PRO32OUT, PW6K1IC, PW6K1R2, PW6K1IN, PW6K1OUT.
  - One (1) PRO32E1PS, PW6K2E2PS.
  - Altronix Power Supplies, Sub-Assemblies.
- Includes Altronix Trove1R Rack Enclosure & one (1) removable THW1R backplane.

### Agency Listings

CE European Conformity

### Features

- Power status LED for use where power and access control boards share the same enclosure
- Simplifies board layout and wire management
- Convenient knockout configuration:
  - Four (4) double knockouts - 3/4" Conduit and 1" Conduit
  - Two (2) double knockouts - 1/2" Conduit and 3/4" Conduit
- 2U drawer on extendable rails
- Included Z Bracket facilitates ease of wiring
- Black powder coated steel enclosure
- Includes cam lock, tamper switch, IEC320 connector and mounting hardware

### Physical and Environmental:

#### Trove1HW1R

##### Dimensions (H x W x D):

Modular 2U standard EIA 19" rack mount chassis

Enclosure:

3.25" x 19.0" x 26.5" (82.6mm x 482.6mm x 673.1mm)

Shipping:

31" x 23" x 8.25" (787.4mm x 584.2mm x 209.6mm)

##### Weights (approx.):

Product: 18 lb. (8.16 kg)

Shipping: 23 lb. (10.43 kg)

#### THW1R

##### Dimensions (H x W x D):

Backplane:

18.5" x 15.25" x 0.375" (469.9mm x 387.4mm x 9.5mm)

Shipping:

18.0" x 13.75" x 1" (457mm x 350mm x 26mm)

##### Weight (approx.)

Product: 4.5 lb. (2.04 kg)

Shipping: 5.2 lb. (2.36 kg)

## Accessories (order separately)



WM5

### WM5, WM25, WM100 - Magnetic Cable Tie Mounts

Altronix WM5, WM25, and WM100 are packs of 5, 25 or 100 magnetic cable tie mounts respectively.

They accommodate standard zip ties or velcro straps. These are ideal for wire management in our Trove series.



RE2

### RE2 - Rack Mount Battery Enclosure

RE2 accommodates up to four (4) 12VDC/7AH batteries.




LC3

### LC3 - Line Cord

18 AWG gauge 6 ft. three-wire line cord with IEC Connector

### Access Controller Position Chart for the Following Models:

Altronix / Honeywell Win-Pak/ProWatch	Pem Mounting
AL400ULXB2, AL400ULXB2V, AL600ULXB, AL600ULXBV, AL1012ULXB, AL1012ULXBV, AL1024ULXB2, AL1024ULXB2V, eFlow4NB, eFlow4NBV, eFlow6NB, eFlow6NBV, eFlow102NB, eFlow102NBV, eFlow104NB, eFlow104NBV	(A)
ACM4, ACM4CB, LINQ8PD, LINQ8PDCB, MOM5, PD4UL, PD4ULCB, PD8UL, PD8ULCB, PDS8, PDS8CB	(B)
PRO42IC, PRO42R2, PRO42IN, PRO42OUT, PW7K1IC, PW7K1R2, PW7K1IN, PW7K1OUT	(C)
PRO42E1PS, PW7K2E2PS	(D)



**Dimensions and Drawing**

Dimensions (H x W x D approximate)

3.25" x 19.0" x 26.5" (82.6mm x 482.6mm x 673.1mm)

