

VertiLine8C Series

AC CCTV Rack Mount Power Supplies



Altronix VertiLine8C Series CCTV Rack Mount Power Supplies provide 8 power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. The units feature individually selectable 24VAC and/or 28VAC power outputs with surge suppression.



VertiLine8C

Key Features

- 115VAC input
- Eight (8) fuse or PTC protected outputs
- 24VAC and/or 28VAC outputs
- Surge protection
- Individual power LED indicators
- Illuminated power disconnect circuit breaker with manual reset
- Removable terminal blocks with locking screw flanges.
- Spare fuses provided (all models with primary and/or secondary fuses)
- UL Listed in the U.S.A. and Canada
- CE European Conformity
- Lifetime Warranty

VertiLine8C Series Configuration Reference Chart

Altronix Model Number	115VAC 60Hz Input Current	Main Fuse Rating	Output Voltage (VAC)	Total Output Current (Power)	Number of Outputs	Current (max. per output)	Fuse Output Protection	Output Fuse Rating	Class 2 Rated Power-Limited Output Protection	Output PTC Rating
VertiLine8C	1.5A	10A	24VAC or 28VAC	5A/32V	8	3A	✓	3A/32V	-	-
VertiLine8CD			24VAC or 28VAC	5A/32V	8	2.5A	-	-	✓	2.5A
VertiLine83C	3A	15A	24VAC or 28VAC	10A/32V	8	3A	✓	3A/32V	-	-
VertiLine83CD			24VAC or 28VAC	10A/32V	8	2.5A	-	-	✓	2.5A

Lifetime Warranty



VertiLine8C Series

AC CCTV Rack Mount Power Supplies



Specifications

Input

Voltage 115VAC, 60Hz

Output

Eight (8) individually selectable power outputs with OFF position

Voltage 24VAC or 28VAC

Current 5A or 10A max. total supply current, see Reference Chart

Protection see Reference Chart

Other Short circuit and thermal overload protection
Filtered and regulated

Indicators (LED)

Master Illuminated master power disconnect circuit breaker with manual reset

Output Eight (8) individual LEDs

Agency Listings

UL UL2044 (Commercial CCTV Equipment)

cUL CSA Standard C22.2 No.1-04, Audio, Video and Similar Equipment

CE European Conformity

Physical and Environmental

Dimensions (H x W x D)

Modular 1U standard EIA 19" rack mount chassis
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)

Weight (approx.)

Model	Product Weight	Shipping Weight
VertiLine8C(D)	6.55 lb. (2.97 kg)	7.85 lbs (3.56 kg)
VertiLine83C(D)	9.3 lb. (4.22 kg)	10.6 lb. (4.81 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr. (approx.):

Model	24VAC	28VAC
VertiLine8C(D)	61	75
VertiLine83C(D)	123	143

Lifetime Warranty