

eBridge PCRX Series

IP and PoE/PoE+ over Coax Solution Multi-Port Receivers



Altronix eBridge4PCRX, eBridge8PCRX, and eBridge16PCRX are four (4), eight (8), and sixteen (16) port EoC Receivers that transmit data and power over coax cable in a PoE compliant format. They are powered by a 48VDC to 56VDC UL Listed limited power source. Units pass PoE/PoE+ up the coax to an eBridge1PCT, eBridge1PCTX or eBridge1ST transceiver. The transceiver, in turn, delivers that PoE compliant power to an edge device/camera. These plug and play units facilitate system upgrades from analog to IP utilizing existing legacy Coax and eliminate the costs and labor associated with installing new network cabling. Data transmission and power over the Coax is possible up to 500m in comparison to 100m Ethernet distance (CAT5e). A maximum range from headend to the edge device/camera is 700m, taking into consideration that up to 100m of structured cable may be deployed from the receiver to the network switch and the transceiver to the edge device/camera.



eBridge4PCRX
eBridge8PCRX
eBridge16PCRX

Key Features

- IEEE 802.3af (15W) and IEEE 802.3at (30W)
- 25Mbps of data at distances up to 500m over Coax
- Eliminates the costs and labor associated with installing new network cabling
- Retrofit digital IP cameras in an analog CCTV installation
- Auto detection and protection of legacy non-PoE cameras/devices
- Works with Megapixel, HD720, HD1080 & VGA (SD) cameras
- Extends Network link distance in an industrial environment
- Upgrades deployed CCTV Coax to a digital network for Retail, Casinos, Airports, Schools, Hospitals, etc.
- UL Listed in the U.S. and Canada
- CE European Conformity
- C-Tick compliant
- Lifetime Warranty

Compatible Transceivers:



eBridge1PCT

eBridge1PCT - IP and PoE over Coax Hardened Transceiver

Delivers IP video/data over coax up to 500m @ 25Mbps.
Supports PoE (IEEE 802.3af).
UL/cUL Listed (UL60950-1). CE and C-Tick Approved.



eBridge1PCTX

eBridge1PCTX - IP and PoE/PoE+ over Coax Hardened Transceiver

Delivers IP video/data over coax up to 500m @ 25Mbps.
Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).
UL/cUL Listed (UL60950-1). CE and C-Tick Approved.



eBridge1ST

eBridge1ST - IP and PoE/PoE+ over Coax Hardened Mini Transceiver

Delivers IP video/data over coax up to 500m @ 25Mbps.
Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).
UL/cUL Listed (UL60950-1). CE Approved.

Lifetime Warranty

eBridge PCRX Series

IP and PoE/PoE+ over Coax Solution Multi-Port Receivers

Specifications

Input

Powered by a 48VDC to 56VDC UL Listed limited power source

Note: Use 54V to 56V power supply to achieve full power per IEEE802.3 at standard

Ethernet

Connectivity: RJ45, auto-crossover

eBridge4PCRX: Four (4) ports

eBridge8PCRX: Eight (8) ports

eBridge16PCRX: Sixteen (16) ports

Wire type: 4-pair CAT5 or better structured cable

Distance: up to 100m

Coax

Throughput is rated to pass 25Mbps of data at distances up to 500m

With proper equipment multiple Megapixel cameras can be used

Speed: 10/100BaseT, half/full duplex, auto negotiation

Connectivity: BNC, RG-59/U or similar

Indicators (LED)

Yellow and Green LED (by RJ45 jack):

IP Link status, 10/100Base-T/active

Green LED: PoE ON

Blue LED: Coax link connection

Agency Listings

UL/cUL

UL 60950-1

(Information Technology Equipment)

CE

European Conformity

Physical and Environmental

Dimensions (W x L x H)

eBridge4PCRX:

Enclosure:

5.25" x 9.25" x 1.7" (133.4mm x 235mm x 43.8mm)

Shipping:

13" x 10" x 6" (330.2mm x 254mm x 152.4mm)

eBridge8PCRX and eBridge16PCRX:

Enclosure:

1.625" x 19.125" x 8.5" (42mm x 486mm x 216mm)

Shipping:

20.25" x 12.5" x 5.5" (514.4mm x 317.5mm x 139.7mm)

Weight (approx.)

Model	Product Weight	Shipping Weight
eBridge4PCRX	1.35 lb. (0.61 kg)	1.7 lb. (0.77 kg)
eBridge8PCRX	5.8 lb. (2.63 kg)	7.8 lb. (3.54 kg)
eBridge16PCRX	7.2 lb. (3.27 kg)	9.2 lb. (4.17 kg)

Temperature

Operating:

- 20°C to 49°C (- 4°F to 120.2°F)

Storage:

- 30°C to 70°C (- 22° to 158°F)

Relative Humidity

85% +/- 5%

Operating Altitude

- 304.8 to 2,000m

Accessories (order separately)



VertiLine563

Vertiline563

Provides input power for eBridge receivers.

Dual independent power supply with optional battery backup.

UL/cUL Listed (UL60950-1). CE European Conformity



Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com