

ENS

SN4432/24P-I



Features and Functions

Professional and Reliable

- New logical and visualized GUI design
- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected

Video Input and Transmission

- Adopt stream over TLS encryption technology (enhanced SDK service and RTP over HTTPS protocol) which provides more secure stream transmission service (max. 128 Mbps TLS stream outgoing bandwidth)
- Up to 32-ch IP cameras can be connected (up to 12 MP)
- Connectable to the third-party network cameras

Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%
- Full channel recording at up to 12MP resolution

HD Video Output

- HDMI Video output at up to 4K (3840 × 2160) resolution

Storage and Playback

- Up to 4 SATA interfaces connectable for HDD connection
- 16-ch synchronous playback at up to 1080p resolution
- Files management
- HDD health monitoring

Smart &POS Function

- Supports multiple VCA (Video Content Analytics) events
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- Supports VCA search for fire/ship/temperature/temperature difference detection triggered video files
- POS information overlay on live view and playback
- POS triggered recording and alarm

Network & Ethernet Access

- Hik-Connect for easy network management
- Gigabit Ethernet network interface
- 24 independent PoE network interfaces are provided