

Hello, we use cookies to improve website performance, facilitate information sharing on social media, and offer advertising tailored to your interests. By using our site, you consent to the use of these cookies. You can also customize your browser's cookie settings. For more information, see our [Privacy Statement](#).

[Click here to not show this message again](#)

Innovation that Endures

Products

- Annunciators & Accessories
- AV Notification
- Communicators
- Control Panels (Addressable)
- Control Panels (Conventional)
- Devices (Addressable)
- Devices (Conventional)
- Mass Notification
- Power Supplies
- Pull Stations
- Releasing Panels
- Wireless (SWIFT)

All Products



W-H355/W-H355R SWIFT Heat Detectors

W-H355 and W-H355R addressable, wireless heat detectors use a state-of-the-art thermistor sensing circuit for a fast response. The W-H355 and W-H355R provide fixed temperature alarm detection at 135°F. The W-H355R also provides Rate-of-Rise Detection at 15°F/min. The W-H355 and W-H355R communicate with the fire alarm control panel (FACP) through a wireless mesh network to the W-GATE wireless gateway. Note: Must be used with an ES-200X, ES-50X, MS-9600(UD)LS or MS-9200UDLS FACP.

[Datasheet](#)
[Manual](#)
[Learn more](#)

Discontinued Products



Download the ECC APP

[Honeywell Power Products](#)

Zoom

[Features & Benefits](#) [Accessories](#) [Documents](#) [Tools](#) [Agencies](#)

W-H355/W-H355R SWIFT Heat Detectors Features and Benefits

- State-of-the-art thermistor technology for fast response.
- Factory preset at 135°F (57°C) for the W-H355 and W-H355R.
- Rate-of-rise triggers at 15°F (8.3°C) per minute for the W-H355R.
- Cascading Mesh Wireless Technology (902-928 MHz frequency).
- Any wireless device can be added to act as a repeater.
- Requires (4) CR-123A batteries (included).

© 2020 [Honeywell International Inc.](#)