Hello, we use cookies to improve website performance, facilitate information sharing on social media, and offer advertising tailored to your interests. By using our site, you consent to the use of these cookies. You can also customize your browser's cookie settings. For more information, see our Privacy Statement.

Click here to not show this message again

# Innovation that Endures

- □ Products

  - AV Notification
  - ☐ Communicators
  - ☐ Control Panels (Addressable)☐ Control Panels (Conventional)
  - ⊕ Devices (Addressable)
  - □ Devices (Conventional)

  - ☐ Power Supplies
  - ☐ Pull Stations
  - ☐ Releasing Panels☐ Wireless (SWIFT)
- ☐ All Products



## W-SD355/W-SD355T SWIFT Photoelectric Smoke Detectors

W-SD355 and W-SD355T addressable, wireless photoelectric detectors use a state of the art photoelectric sensing chamber to provide open area protection. The W-SD355T adds thermal sensors that will alarm at a fixed temperature of 135°F (57°C). The W-SD355 and W-SD355T communicate with the fire alarm control panel (FACP) through a wireless mesh network to the W-GATE wireless gateway. Note: Must be used with an ES-200X, ES-50X, MS-9600(UD)LS or MS-9200UDLS FACP.

Datasheet Manual Learn more

#### Discontinued Products



Download the ECC APP

Honeywell Power Products

#### P Zoom

### W-SD355/W-SD355T SWIFT Photoelectric Smoke Detectors Features and Benefits

- Unique single-source, dual-chamber design to respond quickly and dependably to a broad range of fires.
- Removable cover and insect-resistant screen for simple field cleaning.
- Withstands air velocities up to 4,000 feet-per-minute (20 m/sec.) without triggering a false alarm.
- Factory preset at 1.5% nominal sensitivity for panel alarm threshold level.
- Cascading Mesh Wireless Technology (902-928 MHz frequency).
- Any wireless device can be added to act as a repeater.
- Requires (4) CR-123A batteries (included).

© 2020 Honeywell International Inc.