

7" Touch Screen 5-in-1 Tester

Specifications



Model	MC700-IP-5-S
Display	7" IPS LCD test monitor with touch screen, 1280 x 800 resolution
Network Port	10/100M auto adjust, RJ45
Wi-Fi	Built-in Wi-Fi, speeds 150M, allows you to connect to a wireless network and view IP cameras
IP Discovery	Auto-Scan the whole network segment camera IP
Rapid OnVIF	Search camera quickly, auto log in and display image from the camera
Analog video test	1CH BNC Input & 1CH BNC Output, NTSC/PAL (Auto adapt)
Video Level mete	PEAK video signal level, SYNC signal level, COLOR BURST chroma level measurement for CVBS cameras
Zoom Image	Supports analog and IP camera image zooming & movement
Snapshot, Video Record & Playback	Capture cureent images and record live video as JPG file. Media player will view photos and playbac video
HDMI Output	1CH HDMI Output, supports up to 1080P
PoE power output	48V PoE Power output, Max power 24W
12V/2A Power Output	Output DC 12V/2A power to camera
USB 5V Power Output	5V 2A power output only, NO data
Audio test	1CH audio signal input and 1CH audio signal output to connect headphones
PTZ control	Support RS232/RS485 control, Baud 600-115200bps, Compatible with more than 30 protocols
Color bar generator	Output 1CH PAL/NTSC color bar video signal for testing monitor or video cable (red, green, blue, white and black color)
UTP Cable tester	Test UTP cable connection status and display on the screen. Read the number on the screen
Data Monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal
Network Test	IP address scan, link scan, and Ping test. Quickly search for the IP Camera's IP address on your network
Power	
External power supply	DC 12V (2A)
Battery	Built-in 7.4V Lithium polymer battery, 5800mAh
Rechargeable	After charging 6 hours, normal working time 10 hours
Parameter	
Operation Setting	Capacitive touch screen, OSD menu, select your desired language: English, Chinese, Korean, Russian, Italian or Polish, etc.
Auto Off	5-30 (mins)
General	
Working Temperature	-10℃ ~ 50℃
Working Humidity	30% ~ 90%
Dimension / Weight	243 x 158 x 48(mm) / 620g

Key Features

- 7 inch touch screen IP / AHD / TVI / CVI / Analog tester
- 1280*800 resolution
- IP discovery, it can auto scan the whole network segment IP, and auto modify tester's IP address
- Rapid ONVIF, search camera quickly, auto log in and display image from the camera
- Combine with more than 80 brand cameras test
- Video level meter, PEAK video signal level, SYNC signal level, Color bar chroma level measurement (Optional)
- UTP Cable test, Test UTP cable connection status and display on the screen
- DC 12V 2A power output, PoE power output
- TDR tester, easy to check the network cable and BNC cable etc problem, Digital Multi-meter, Optical power meter, Visual fault detector function, effective to solve the optical fiber transmission problem
- CCTV test: snapshot, video record and playback, zoom, camera OSD menu contorl over coaxial cable
- Resolution:
HD-TVI: 720P 25,30,50,60fps / 1080P 25,30fps
AHD: 720P 25,30fps / 1080P 25,30fps
HD-CVI: 720P 25, 30, 50, 60fps / 1080P 25, 30fps
SDI: 720P 25, 30, 50, 60fps / 1080P 25, 30fps
- Built-in browser, RTSP protocol
- Supports more than 80 IP Camera brands test
- IPC view
- Built-in manual, easy to read at any time

Design and specifications are subject to change without notice.

www.EasternCCTV.com

Headquarters

50 Commercial St.,
Plainview, NY 11803

TEL: 516-870-3779 FAX: 516-390-1200

Queens, NY

129-04 14th Ave.,
College Point, NY 11356

TEL: 718-939-2710 FAX: 718-939-2713

E. Los Angeles, CA

110 California Ave.,
City of Industry, CA, 91744

TEL: 626-961-8810 FAX: 626-961-8809

N. Hollywood, CA

13761 Saticoy St.
Panorama City, CA 91402

TEL: 818-924-9021 FAX: 818-849-5127

Miami, FL

4515 NW 72nd Ave.
Miami, FL 33166

TEL: 305-423-1329 FAX: 786-717-7282

Houston, TX

3790 Westchase Dr.,
Houston, TX 77042

TEL: 832-308-5282 FAX: 832-925-7454