

UN-IPC3614SR3DPF28(36)(60)M

4MP Network IR Fixed Dome Camera



Specifications

Model	UN-IPC3614SR3DPF28M	UN-IPC3614SR3DPF36M	UN-IPC3614SR3DPF60M
Camera			
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS		
Lens	2.8mm@F2.0	3.6mm@F2.0	6.0mm@F2.0
DORI Distance	Lens (mm)	Detect (m)	Observe (m)
			Recognize (m)
			Identify (m)
Angle of view(H)	104.4°	76.5°	49.9°
Angle of View (V)	67°	53.2°	32.9°
Angle of View (O)	135.7°	99.5°	61.4°
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°
Adjustment Range	Pan: 0°~360°, Tilt: 0° ~ 77°, Rotation: 0° ~ 360°		
Shutter	Auto/Manual, 1 ~ 1/100000s		
Minimum Illumination	Colour: 0.02Lux (F2.0, AGC ON) 0Lux with IR		
Day/Night	IR-cut filter with auto switch (ICR)		
Digital noise reduction	2D/3D DNR		
S/N	>52dB		
IR Range	Up to 30m (98ft) IR range		
Defog	Digital Defog		
WDR	120dB		
AWB (Auto white balance)	Auto/manual		
Gain Control	Auto/manual		
Video			
Video Compression	Ultra 265, H.264, MJPEG		
H.264 code profile	Baseline profile, Main Profile, High Profile		
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; 4MP (2560*1440), Max 25fps; 3MP (2048*1520), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps		
HLC	Supported		
BLC	Supported		
9:16 Corridor Mode	Supported		
OSD	Up to 8 OSDs		
Privacy Mask	Up to 8 areas		
ROI	Up to 8 areas		
Motion Detection	Up to 4 areas		
Smart			
Behavior Detection	Intrusion, cross line, motion detection		
Intrusion	Enter and loiter in a pre-defined virtual region		
cross line	Cross a pre-defined virtual line		
motion detection	Moving within a pre-defined virtual region		
Recognition	Face detection, Audio detection		
Intelligent Identification	Defocus, Scene Change, Object Left, Object Moving		
Statistical Analysis	People counting		
General Function	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTPS Authentication, User Authentication		
Network			
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS		
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API		
Interface			
Network	1 RJ45 10M/100M Base-TX Ethernet		
General			
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5W		
Dimensions (Ø x H)	Φ126 x 94mm (Ø5.0" x 3.7")		
Weight	0.45kg (0.99lb)		
Operating Conditions	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)		
Ingress Protection	IP67		

Key Features

- 1/3" HD CMOS Sensor
- Up to 2592 × 1520 resolution, 20fps
- 2.8 / 3.6 / 6.0mm Fixed Lens
- WDR, Smart IR, Distance: 30m
- ONVIF
- DC12V, PoE
- IP67

Dimensions

