



VISTA-250FBPT

VISTA® Commercial Partitioned Fire and Burglary Alarm Control Panel

The VISTA-250FBPT provides the ultimate protection for life and property. This commercial fire and burglary control panel supports up to eight partitions and up to 250 zones/points using hardwired, wireless and V-Plex® addressable technologies. A diverse line of Honeywell Home initiating devices, notification appliances, communication devices, keypads, RF receivers and relays satisfy a wide range of installation requirements.

The VISTA-250FBPT control is suitable for fire-only applications, as well as for installations requiring integrated fire/burglary systems. It is the perfect solution for medical and professional office buildings, churches and synagogues, banks, schools, strip malls, and factory or warehouse environments.

VISTA-250FBPT is compatible with a number of AlarmNet® communication products for alarm reporting, uploading/downloading and Resideo Total Connect Remote Services.



FEATURES AND BENEFITS

- Eight hardwired zones standard, expandable to 250 using V-Plex addressable points/zones
- Supports up to 250 wireless zones (fewer if using hardwired and/or V-Plex zones)
- Can control eight separate areas independently (8 partitions)
- Common lobby partition – auto arm or disarm based upon assigned partitions
- Master partition – used for viewing status of all partitions
- Supports commercial wireless fire and burglary devices
- Stores up to 1000 events
- Accommodates 250 user codes and up to 500 access card holders using VISTAKEY®
- Supports V-Plex addressable VISTAKEY access control (1 to 15 doors)
- Two on-board NACS delivering a total of 2.3A @ 12V
- Automatic smoke detector sensitivity maintenance testing
- Four-wire smoke reset using on-board Form C relay
- Supports Dynamic Signaling for AlarmNet Communicators
- Supports Internet and GSM alarm reporting
- Supports graphical user interfaces for burglary use (e.g. 6280 and Tuxedo Touch™)
- Supports 6160CR-2 multi-LED fire keypad
- Upload/download via AlarmNet® Communicators
- Carbon monoxide (CO) zone support
- On-board serial port for communication with WIN-PAK®, Pro-Watch® and approved third-party applications
- Supports Total Connect Remote Services*
*Event reporting only for fire partition.

VISTA-250FBPT

VISTA® Commercial Partitioned Fire and Burglary Alarm Control Panel

ADDITIONAL FEATURES

- Notification Appliance Circuits (two):
 - Programmable
 - Individually silenceable
- False alarm reduction features:
 - Exit error logic
 - Exit delay reset
 - Cross zoning
 - Call waiting defeat
 - Recent close report
- Supports commercial hardwired, addressable V-Plex® polling loop and wireless zones
- Hardwired zones
 - Provides eight style B hardwired zones
 - EOLR supervised for Fire and UL burglary installations
 - Supports N.O. or N.C. sensors
 - Individually assignable to any of eight partitions (all fire zones on partition 1)
 - Up to 16 conventional two-wire smoke detectors each on zone one and two (32 total)
- Patented addressable V-Plex polling loop technology
 - Class B, Style 3 SLC
 - Supports 242 two-wire addressable points
 - Global polling technology for faster processing
 - Supervised by panel
 - Zones individually assignable to partitions and notification circuit (bell) output or auxiliary relay
 - 4,000 ft. capability without the use of shielded cable
 - Extender/Isolation bus modules
 - Eight zone - Class A and B expander module
 - Eight zone - Class B expander module
 - Single-zone supervised contact module
 - Single relay module for auxiliary fire functions
 - Supports anti-masking feature on "smart" motion detectors (e.g. DT7500SN)
- UL Listed wireless expansion
 - Supports up to 250 wireless zones/points
 - Supervised by control for check-in signals
 - Tamper protection for transmitters
 - Individually assignable to one of eight partitions
 - Supports commercial wireless smoke detectors
- Up to 15 doors using VISTAKEY® V-Plex Access Control
- Event reporting
- Local printer for event log printing
- Communication
 - Phone line, GSM and IP communicator support
 - Panel operation during download
 - Four or 10-digit subscriber account numbers
- Extra security feature that requires master code to allow installer into program mode (enabled through Compass Downloader)

VISTA-250FBPT Technical Specifications

Electrical:

Primary power: 18VAC @ 72VA

Honeywell Home No. 1451-UL9

Control panel quiescent current

draw: 300mA

Backup battery:

12VDC, 12AH min to 34.4AH max

Lead acid battery (gel type)

Alarm power: 12VDC, 1.7A max for

each notification (bell) circuit output

Total 2.3A @ 12V

Aux. standby pwr: 12VDC, 1A max

Total power: 2.3A at 12VDC

Standby time: 24 hours with 1A

standby load using 34.4AH battery

Fusing: Battery input, aux. and

notification (bell) circuit outputs are

protected using PTC circuit protectors.

All outputs are power limited.

Optional 24-volt kit

Communications:

Dialer

Line seize: Double Pole

Ringer equiv: 0.7B

Formats: ADEMCO Low Speed,

ADEMCO 4+2 Express, ADEMCO High

Speed, ADEMCO Contact ID, Sescoa

and Radionics

Dual phone line capability using
5140DLM module

AlarmNet® Communicators: GSM,

i-GSM and IP Communicators

Cabinet Dimensions:

18" H x 14.5" W x 4.3"D

Environmental:

Storage temp: 14°F to 158°F (-10°C
to 70°C)

Operating temp: 32°F to 122°F (0°C
to 50°C)

Humidity: 85% RH

EMI: Meets or exceeds the following
requirements:

FCC Part 15, Class B Device

FCC Part 68

IEC EMC Directive

Agency Listings:

UL864 – Control Units and Accessories
for Fire Alarm Systems

ULC-S559-04 – Equipment for Fire
Signal Receiving Centers and Systems

UL1076 – Proprietary Burglar Alarm
Units and Systems

UL1610 – Central Station Burglar
Alarm Units

CAN/ULC-S304-06 – Signal Receiving
Centre and Premise Burglar Alarm
Control Units

UL1635 – Digital Alarm Communicator
System Units

UL365 – Police Station Connected
Burglar Alarm Units and Systems

UL609 – Local Burglar Alarm Units and
Systems

UL985 – Household Fire Warning
System Units

UL1023 – Household Burglar Alarm
System Units

ULC-S545-02 – Residential Fire
Warning System Control Units

ULC/ORD-C1023-74 – Preliminary
Standard for Household Burglar Alarm
System Units

ULC-S303-M91 – Standard for Local
Burglar Alarm Units and Systems

Factory Mutual (FM)

California State Fire Marshal (CSFM)

FDNY Certificate #6140

VISTA-250FBPT Compatible Devices

Auxiliary Devices:

6160CR-2 – Red Fire Keypad
 6160 – Burglary Keypad
 6280, Tuxedo Touch™, Tuxedo Touch with Wi-Fi® Graphic Keypads – Burglary
 4204 – Relay Module, four Form C contacts
 4204CF – Two supervised NAC circuits
 5881ENHC Series RF receivers
 5883H RF receiver
 6220S – System printer

Two-wire Conventional Smoke Detectors:

System Sensor
 ESL
 DSC

Horn/Strobes:

System Sensor
 Wheelock
 Gentex

Manual Pull Stations:

5140MPS-1
 5140MPS-2

V-Plex® (Addressable) Devices:

4208U Universal Eight-zone Expansion Module
 4208SN Eight-zone Expansion Module
 4208EX Universal Eight-zone Expansion Module (Canada)
 4101SN Single Relay/Zone Module
 4208SNF Class A/B Expander Module

4190SN Remote Point Module – two zones
 4193SN and 4193SNP Two-zone Expander Modules

V-Plex Extender/Isolation Modules:

4297 Extender/Isolator Module
 VSI Isolator Module

V-Plex Smoke Detectors:

5193SD
 5193SDT
 5192SDTA

V-Plex Passive Infrared Detectors:

IS2500SN
 DT7500SN

V-Plex (Addressable) Contacts:

4939SN-WH
 4959SN

V-Plex Glassbreak Detectors:

FG1625SN

Seismic Detectors:

SC100
 SC105

Commercial Wireless Devices:

5808W3/5808W3A – Photoelectric Smoke/Heat Detector
 5806W3 – Photoelectric Smoke Detector
 5809 – Wireless Heat Detector
 5817CB – Wireless Commercial Transmitter

5869 – Hold-Up Transmitter
 5800CO/5800COA – Carbon Monoxide Detector
 5800PIR-COM – Commercial PIR

Access Control:

VISTAKEY® V-Plex® (addressable) Access Control
 VISTAKEY-SK Starter Kit
 VISTAKEY-EX Expansion Kit
 Integrates with WIN-PAK® and Pro-Watch® systems

Alarm Communications U.S.:

GSMV4G – Digital Cellular Communicator with Two-way Voice Transport Capability
 iGSMV/iGSMV4G – Internet and Digital Cellular Communicator
 iGSMCF/iGSMCFP4G – Commercial Fire Digital Cellular Communicator with Internet
 iGSMHS//iGSMHS4G – High Security Internet and Digital Cellular Communicator
 7845i-ENT – Internet/Intranet Enterprise Communicator
 7847i – Internet Communicator Canada
 GSMV4GCN – Digital Cellular Communicator with Two-way Voice Transport Capability
 iGSMVCN/iGSMVCN4G – Internet and Digital Cellular Communicator

Product specifications subject to change.

ORDERING

V250FBPT	Commercial Fire and Partitioned Burglary Alarm Control Panel 12V Model
V250FBPT24KT (U.S. Only)	Commercial Fire and Partitioned Burglary Alarm Control Panel with External 24V Power Supply (6A, four outputs, synchronized)

For more information

security.honeywellhome.com/hsc



Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100
 P.O. Box 9040
 Melville, NY 11747
 1-800-645-7492
resideo.com

L/VS250FBPTD/D | 06/19
 © 2019 Resideo Technologies, Inc.
 This product is manufactured by Resideo and its affiliates. The Honeywell Home trademark is used under license from Honeywell International Inc. All rights reserved.

