



Make sure all your Infinity Control Modules only operate when necessary by wiring them to this keyed switch.

SPECIFICATIONS

Compatible with all IAM and IAV units. Must be used with at least one ICMHOA. Controls any ICMHOA module receiving its operating 24 VDC through the ICMENGAGE. Interrupts the positive supply to the ICMHOA modules, rendering them inoperative until activation of the ICMENGAGE. If an ICMLEDTST and an ICMENGAGE are both installed, the ICMENGAGE must be wired electrically after the ICMLEDTST. Standard clinch type terminal strip used for field wiring.



FEATURES

- Scratch-resistant Lexan® face panel with a black background and white screened legend
- Durable steel frame mounts into an Infinity Gang Box or standard electrical back box and securely holds the Infinity Gang Plate
- Standard mounting hardware included



SWITCH POWER RATINGS

3A @ 24VDC | 3A @ 24VAC

TERMINAL BLOCK

16-22 AWG wire

AGENCY APPROVALS

- UOXX.S2580 UL Listed Control Unit Accessories
- UUKL.S2580 UL Listed Smoke-Control System Equipment
- 7120-0553:0105 California State Fire Marshal (CSFM)

ORDERING INFORMATION

Part #	Description
ICMENGAGE (SSU02521)	Keyed Engage Switch