


VITALink®

16 AWG 2-Conductor Non-Shielded Circuit Integrity Cable



1. Construction:

- 1.1. Conductors: 16 AWG (1.31 mm²) Solid Bare Copper, 0.0508" (1.27 mm) Nominal Diameter
- 1.2. Tape: Flame Retardant Tape
- 1.3. Insulation: Low Smoke Zero Halogen Thermoset Fire-Roc® 0.128" (3.25 mm) Nominal Diameter & 0.029" (0.73 mm) Nominal Wall Thickness
- 1.4. Color Code: Red, Black
- 1.5. Cable Assembly: Cable (2) Conductor 4.5" (114 mm) Nominal LHL
- 1.6. Jacket: Non Halogen Flame Retardant Polyolefin Compound, Nominal Overall Diameter, 0.321" (8.15 mm), Nominal Wall Thickness 0.034" (0.86 mm) Color: RED

1.7. JACKET Print:

COMTRAN LSZH VITALink® FPLR-CI-ST1
 CMR-CI-LS CL3R-CI-ST1 2/C 16AWG 105C SUN RES
 WET or FAS105 LL14444 FRR-2HR
 FHIT.40A/FHIT7.40A UL2196/ULC S139 MAX
 VOLTAGE 72V PN35777 --- NYC APPROVED (MMYY)
 000002 (01-12345)

NOTE: MMY Y is 4 Digit Month/Year
 Sequential Footage Markings Every Two Feet
 (01-12345)- Traceability Marking

2. Compliance:



- 2.1. (UL) Listed Type FPLR-CI-ST1
- 2.2. (UL) Listed Type CMR-CI-LS
- 2.3. (UL) Listed CL3R-CI-ST1
- 2.4. CSA Listed FAS 105
- 2.5. UL Subject 1424 Power Limited Fire Alarm Circuits; 300V/105°C Classified
- 2.6. UL Subject 13 Power Limited Circuit Cables; 300V/105°C Classified
- 2.7. UL Subject 444 Communications Cable; 300V/105°C Classified
- 2.8. ANSI/UL 2196 2-Hour Fire Rating for use in FHIT System 40A
- 2.9. CAN/ULC-S139 2-Hour Fire Rating with Hose Stream for use in FHIT7 System 40A
- 2.10. NFPA 70 & 72
- 2.11. NFPA 130
- 2.12. NFPA 502
- 2.13. California State Fire Marshal Approved
- 2.14. NYC Electrical Advisory Board #54502, April 2017
- 2.15. RoHS Compliant

3. Physical Characteristics:

- 3.1. Nominal Weight per 1000 FT: 52 Lbs. (23.5 kg)
- 3.2. Min Bend Radius: 3" (76.2 mm)
- 3.3. Maximum Pull Tension – Straight runs: 41 Lbs. /ft. (18.5 mm)

4. Physical Characteristics:

- 4.1. Nominal Conductor DCR @ 68F (20° c): 4.09 Ω / 1000 Ft.
- 4.2. Nominal Capacitance C-C: 19pF/Ft.

TITLE:		DESCRIPTION:		COMTRAN			
DS35777		16 AWG 2 Conductor Non-Shielded VITALink® Circuit Integrity Cable		330A Turner Street South Attleboro, MA 02703 Phone: 508-399-7004 Fax: 508-399-8839		<small>Innovative Systems. Engineered Solutions.</small>  <small>A Marmon Wire & Cable/Berkshire Hathaway Company</small>	
Rev	Date	Detail	Eng.	App.			
12	05/12/20	Update legend due to UL update	PB	KB	ECN 20-042		
11	07/09/19	Change legend per UL update; add electrical data	PB	WC	ECN 19-071		
10	02/27/19	Add regulatory approvals	PB	WC			
09	12/19/18	Change logo and basic corrections	SM	WC			
08	10/31/18	Add LL# to print	PB	WC	ECN 18-118		
07	05/24/18	FAS 90 to 105	PB	WC	ECN 18-067		

Comtran reserves the right to change the information above without prior notification. Comtran assumes no risk, and is not liable for direct or indirect, or consequential damages, resulting from the use of this document