

### Features

- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- Bed clips included
- UL® 1069 Listed; SF301A is also UL® 2560 Listed

### Description

The TekTone SF301A (single) or SF302 (double) call cords are for use with the Tek-CARE® nurse call systems and wireless emergency call systems, where ¼" phono jacks are used. Ten-foot cords are also available as SF301A/10 and SF302/10. The SF301A and SF302 are oxygen safe call cords certified safe for use by all patients receiving oxygen therapy. These waterproof and impact resistant call cords have completely sealed push buttons.

### Listings



SF301A is UL® 1069 and UL® 2560 Listed;  
SF302 is UL® 1069 Listed; UL® File Number  
E71599.

### Specifications

Dimensions: 7' (2.13 m) long polyvinyl covered cord  
Construction: SPST-1A switch, Integral brass, fine silver contacts 1 AMP, 115 watt maximum, AC  
Connections: ¼" (6.35 mm) plug-in phono jack



SF301A, SF302 Call Cord

### Required Components

Tek-CARE®500 Wireless Nurse Call System  
with SF521UL or SF523UL Room Stations

Tek-CARE®120 or 160 Nurse Call System  
with SF121 or SF122 Room Stations

Tek-CARE®300II Nurse Call System  
with SF380A Patient Stations

Tek-CARE® NC200N or NC150N Nurse Call Systems  
with IR151B or IR152B Patient Stations

Tek-CARE® NC110N Nurse Call System  
with SF100C or SF102 Patient Stations