

Intelligent Detection Devices

Intelligent Remote Alarm Lamps Models RLI-1 and RLI-2

ARCHITECT AND ENGINEER SPECIFICATIONS

- Multi-color light-emitting diodes (LEDs) (green, amber and red) mimics detector
- Becomes a second accessory
 - used with relay or audible base
- Can be addressed and independently controlled by panel logic
- **UL Listed, ULC Listed;**
FM, CSFM and NYC Fire Dept. Approved



Model RLI-1



Model RLI-2

Product Overview

The Siemens — Fire Safety Division Intelligent Remote Lamps (Model RLI-1 for ceiling-mount; Model RLI-2 for wall-mount) are designed for use with initiating devices that are concealed or otherwise not easily within view (e.g. — above suspended ceilings, under sub-floors, in unexposed ventilating ducts, normally locked vaults or closed rooms, etc.)

Both of these intelligent lamps operate with the Siemens MXL family of fire alarm control panels.


Model RLI-1 is mounted on a 4" (10.2 cm.) octagon outlet box, and Model RLI-2 is mounted on a single-gang electrical box. Although there is no mounting limitation, Model RLI-1 is often ceiling mounted, and Model RLI-2 is wall mounted.

Specifications

Model RLI-1 shall mount on a standard 4-inch, (10.2 cm.) octagon conduit box, and Model RLI-2 on a standard, single-gang switch box. The wiring between the remote alarm lamp and the initiating device shall be #18 American Wire Gauge (AWG) thermoplastic-fixture wire enclosed in conduit, or #18 AWG limited-energy, shielded cable without conduit (if permitted by local building codes).

Installation wiring shall be as indicated in system drawings.

Mounting Diagrams



Models RLI-1 and RLI-2 have screw-type terminals for ease of installation. The mounting plates of both units are off-white plastic and present an unobtrusive appearance that will blend with any ceiling or wall décor.

Temperature and Humidity Range

Both Intelligent Remote Lamps are UL 864 9th Edition Listed for indoor dry locations within a temperature range of 120+/-3°F (49+/-2°C) to 32+/-3°F (0+/-2°C) and a relative humidity of 93+/-2% at a temperature of 90+/-3°F (32+/-2°C).

Details for Ordering

Model Number	Part Number	Description	Shipping Weight	
RLI-1	500-390673	Intelligent Remote Lamp, Ceiling	0.5 Lb.	0.3 Oz.
RLI-2	500-390674	Intelligent Remote Lamp, Wall	0.5 Lb.	0.3 Oz.

Intelligent Remote Alarm Lamps **3515**

This Page Left Intentionally Blank

Notice: This marketing data sheet is not intended to be used for system design or installation purposes. For the most up-to-date information, refer to each product's installation instructions.

SIEMENS Industry, Inc.
Building Technologies Division

Fire Safety
8 Fernwood Road
Florham Park, NJ 07932
Tel: (973) 593-2600
FAX: (908) 547-6877
URL: www.usa.Siemens.com/Fire

SII-FS
Printed in U.S.A.

Fire Safety
2 Kenview Boulevard
Brampton, Ontario
L6T 5E4 / Canada
Tel: (905) 799-9937
FAX: (905) 799-9858

July 2013
Supersedes sheet dated 3/12
(Rev. 2)