


# IP-5IR4S41-28

4MP IR Water-Proof Bullet Network Camera



## MODEL(S) AVAILABLE

IP-5IRD4S44-28

## KEY FEATURES

- ▶ H.265 /H.264/MJPEG coding
- ▶ Max.resolution: MP ( 2560 × 1440)
- ▶ ICR auto switch, True day / Night vision
- ▶ 3D DNR, WDR, HLC, BLC, smart IR, etc.
- ▶ Max. IR distance: 98 ft (30 m)
- ▶ Built-in micro SD card slot, up to 256 GB
- ▶ 1CH Built-in Mic; 1CH Audio input
- ▶ 12V DC / PoE power supply
- ▶ IP67 ingress protection
- ▶ Support three streams
- ▶ Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- ▶ Intelligent analytics

## Product Specifications

Camera	
Image Sensor	1/3" 4MP CMOS
Image Resolution	2560 (H) × 1440 (V)
Electronic Shutter	1/2 s ~ 1/100,000 s
Minimum Illumination	0.005 lux @ F1.6, AGC ON; 0 lux with IR
Smart IR	Yes
IR Distance	98 ft (30 m)
Lens Type	Fixed
Iris Type	Fixed Iris
Focal Length	2.8 mm, 3.6 mm
Angle of View	Horizontal: 94.0°
	Vertical: 50.0°
	Diagonal: 115.0°
Max. Aperture	F1.6
Pan / Tilt / Rotation	Pan:0° ~ 360°; Tilt:0° ~ 75°; Rotation:0° ~ 360°

Compression Standards	
Video Compression	H.265 / H.264 / MJPEG
Streaming Capability	3 Streams
Video Frame Rate	<b>Main Stream:</b> 4MP/3MP/1080P/720P @ 25/30 fps
	<b>Sub Stream:</b> 720P/D1/CIF @ 25/30 fps
	<b>Third Stream:</b> D1/CIF/480×240 @ 25/30 fps
Video Resolution	4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, 480×240, CIF
Video Bitrate	64 Kbps ~ 8 Mbps
Video Bitrate Type	VBR / CBR

Image and Feature Support	
Wide Dynamic Range	120 dB true WDR
Day / Night	ICR
BLC Mode	Yes
HLC Mode	Yes
Digital Noise Reduction	3D DNR
Motion Detection	Yes
Electronic Image Stabilization	N/A
Defog	N/A
Digital Zoom	N/A
Flip	Yes
Mirror	Yes
Privacy Masking	N/A
Image Rotation	N/A
ROI	Each ROI to be configured separately
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
IPC Alarm	N/A
Alarm Input	N/A
Alarm Output	N/A
Audio Compression	1CH audio input


Network & Interface	
Ethernet	RJ-45
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTPS, QoS
Network Interoperability	ONVIF
Streaming Method	N/A
Network Max. Users	3
Storage	Built-in Micro SD Card (support max. 256 GB)
Video Output	N/A
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, corridor pattern
Audio Interface	1/1
Built-in MIC	Yes
RS485	N/A
Reset Button	Yes

General	
Power Supply	12 V DC / PoE
Power Consumption	< 5 W
Operating Temperature	-30 ~ 60°C (-22 ~ 140°F) / Less than 95% RH
Storage Temperature	-30 ~ 65°C (-22 ~ 149°F) / Less than 95% RH
Ingress Protection	IP67
Casing	-
Dimensions	167.5 mm × 74.5 mm × 74.5
Net Weight	Approx. 0.38 kg (0.83 lb)
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

Product Accessories




B15-W



B8-W

Product Dimensions ( mm )



**Plainview, NY**  
 50 Commercial St., Plainview, NY 11803  
 Tel: 516-870-3779

**Downtown LA, CA**  
 1113 Venice Blvd., Los Angeles, CA 90015  
 Tel: 213-218-2260

**Miami, FL**  
 1604 NW 84 Ave., Doral, FL 33126  
 Tel: 786-410-6777

**College Point, NY**  
 129-04 14th Ave., College Point, NY 11356  
 Tel: 718-939-2710

**San Francisco, CA**  
 41324 Christy St., San Francisco, CA 94538  
 Tel: 510-584-9007

**Chicago, IL**  
 873 Cambridge Dr., Elk Grove Village, IL 60007  
 Tel: 847-584-2227

**Brooklyn, NY**  
 9017 5th Ave., Brooklyn, NY 11209  
 Tel: 347-507-5533

**Houston, TX**  
 1720 Townhurst Dr., Houston, TX 77043  
 Tel: 430-702-0999

**City of Industry, CA**  
 525 Parriott Pl., City of Industry, CA 91745  
 Tel: 626-961-8999

**Dallas, TX**  
 12901 Valley Branch Ln., Farmers Branch, TX 75234  
 Tel: 972-996-1600