

# INCC-TEL

## Fire Fighter Telephone Module

### General

The Gamewell-FCI, INCC-TEL is a compact Fire Fighter Telephone Module that is used in emergency evacuation, command centers. It provides an easy-to-use selective telephone and offers voice paging to selected speaker zones. This module is a component of the following Systems.

- E3 Series® Expandable Emergency Evacuation System
- E3 Series Combined Fire and Mass Notification System
- E3 Series Broadband Voice Evacuation System

The INCC-TEL provides a cost-effective fire fighter telephone interface. It offers a voice paging capability that is used with the following Systems:

- E3 Series Fire Command Center
- Voice Evacuation for Mass Notification Systems used with the E3 Series, Local Operating Console

When the INCC-TEL is installed with the ASM-16 Addressable Switch Module, it provides an easy-to-use selective telephone and offers voice paging to selected speaker zones. The LEDs display the telephone and paging status.

### Installation

The INCC-MIC TEL Fire Fighter Telephone Module can be installed in any of the following types of E3 Series cabinets:

- Cabinet AA
- Cabinet B
- Cabinet C
- Cabinet D

### Ordering Information

**1100-0451:** Fire Fighter Telephone Module



INCC-TEL

## FEATURES & BENEFITS

- Listed under UL® Standard UL2572 for Mass Notification
- Listed under UL Standard 1869 9th Edition
- Includes the following:
  - pre-assembled fire fighter telephone
  - steel box enclosure
  - telephone handset holder
- Contains a terminal block with an easy-to-use wiring cable
- Delivers audio feedback cancellation
- Offers a simple and quick installation
- Provides a supervised phone

# INCC-TEL Technical Specifications

## SYSTEM

**INCC-TEL:** Fire Fighter Telephone Module

**INCC-TEL Box :** Durable gauge steel construction with telephone hand set holder

**Dimensions:** 10.96"W x 6.48"H x 2.45"D  
(27.8 W x 16.45 H x 6.22 D cm)

**Operating Current:** .020 amps

## TEMPERATURE AND HUMIDITY RANGES

This system meets NFPA requirements for operation at 0 – 49°C/32 – 120°F and at a relative humidity 93% ± 2% RH (non-condensing) at 32°C ± 2°C (90°F ± 3°F).

However, the useful life of the system's standby batteries and the electronic components may be adversely affected by extreme temperature ranges and humidity. Therefore, it is recommended that this system and its peripherals be installed in an environment with a normal room temperature of 15 – 27°C/60 – 80°F.

## STANDARDS

The INCC-TEL is designed to comply with the following standards:

**UL Standards:** 864 9th Edition  
2572 for Mass Notification

## AGENCY LISTINGS AND APPROVALS

These listings and approvals apply to the modules specified in this document. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. Consult the factory for the latest listing status.

**UL Listed:** S1869  
UL 2572 for Mass Notification

**MEA FDNY Approved:** COA # 6077

**ISO 9001 Certification**

For a complete listing of all compliance approvals and certifications, please visit:

<http://www.gamewell-fci.com/en-US/documentation/Pages/Listings.aspx>

E3 Series® and Gamewell-FCI® are registered trademarks of Honeywell International Inc.

UL® is a registered trademark of Underwriter's Laboratories Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

## For more information

Learn more about Gamewell-FCI's INCC-TEL and other products available by visiting [www.Gamewell-FCI.com](http://www.Gamewell-FCI.com)

## Honeywell Gamewell-FCI

12 Clintonville Road  
Northford, CT 06472-1610  
203.484.7161  
[www.honeywell.com](http://www.honeywell.com)

9020-60569 | D | 09/17  
©2017 Honeywell International Inc.

**Honeywell**