



Features

- **New** robust and tactile membrane switches
- 4 line by 20-character LCD display
- Backlit display
- User-friendly Menu
- Common Control buttons with selector switches and LEDs
- Four Status Queues: Alarm, Supervisory, Trouble and Monitor
- Occupies one display position in the BBX-FXMNS enclosure
- Compatible with FX-2000, FleX-Net™ (FX-2000N) and MMX Fire Alarm panels

Description

The DSPL-420DS Main Display Module provides a 4 line by 20-character backlit LCD display, Common Control buttons and Four Status Queues with selector switches and LEDs for Alarm, Supervisory, Trouble and Monitor. The DSPL-420DS occupies one display position in the BBX-FXMNS enclosure.

The DSPL-420DS comes with a user-friendly menu. Common Control switches and/or indicating LEDs for System Reset, Signal Silence, Fire Drill, Acknowledge, General Alarm, Lamp Test, A.C. On, Pre-Alarm and Ground Fault.

Power Consumption

	Amps (24VDC)
Stand by	30 mA
Alarm	30 mA



Ordering Information

Model	Description
DSPL-420DS	4 Line by 20 Character Backlit LCD Display

Canada
 25 Interchange Way Vaughan, ON L4K 5W3
 Telephone: (905) 660-4655 | Fax: (905) 660-4113

U.S.A.
 4575 Witmer Industrial Estates Niagara Falls, NY 14305
 Toll Free: (888) 660-4655 | Fax Toll Free: (888) 660-4113

www.mircom.com



THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.

CATALOG NUMBER **5332**

Rev. 1