

by Honeywell

FCI C4 and D4 Series Cabinets

Description

These cabinets, designed to house the Fire Control Instruments NetSOLO™ Classic Emergency Voice Evacuation AA Series amplifiers, are fabricated from 16-gauge steel.

The cabinet assembly consists of two parts: a backbox and a solid, locking door.

Cabinets are available in black or red. This selection provides a stylish combination to accent the décor of the finest lobby setting.

The key-locked door includes a pin-type hinge, two keys and hardware to mount the door to the backbox. Right or left hand hinges are selectable in the field.

The backbox is engineered to provide ease-ofentry for the installer. Knockouts are positioned at numerous points to easily aid the installer in bringing a conduit into the enclosure.

Specifications

Dimensions	C4 Cabinet	D4 Cabinet
Height	37.13" (94.3 cm)	45.90" (116.5 cm)
Width	24" (61 cm)	24" (61 cm)
Depth	5.20" (13.9 cm)	5.20" (13.9 cm)

Ordering Information

Model	Description
FCI-DR-C4B	Door, lock & key for SBB-C4, black
FCI-DR-C4BR	Door, lock & key for SBB-C4, red
FCI-CR-D4B	Door, lock & key for SBB-D4, black
FCI-CR-D4BR	Door, lock & key for SBB-D4, red
SBB-C4	Backbox, accepts 3 amplifiers, black
SBB-D4	Backbox, accepts 4 amplifiers, black

NetSOLO™ is a trademark of Fire Control Instruments.

Amplifier Cabinets for NetSOLO™ Classic Voice Evacuation System



Model FCI-D4-D4B door with SBB-D4 backbox

Features

- 16-gauge steel backbox with integral trough offset.
- 90° opening door with zero clearance; 180° opening door with full clearance.
- Removable doors with zinc die-cast hinges.
- Backbox and door ground studs provide positive ground.
- Slotted quarter-turn latch and key lock.

An ISO 9001-2000 Company

