

FACP Accessories

PAD-3 Distributed Power Supply Unit Notification Appliance Circuit

Models PAD-3, PAD-3R, PAD-3-MB, EN-PAD, EN-PAD-R

Architect and Engineer Specifications

- 24VDC output voltage
- Ground-fault detection
- Advanced microprocessor control
- Power supply supports NAC power
 - Up to 6A @ 170W, via Siemens Model PAD-3
- 3 Amps of auxiliary-power output
- 'Form C' Trouble monitoring dry contact
- Four (4), power-limited notification appliance circuits (NACs)
- Power supply supports NAC power
 - Up to 6A @ 170W, via Model PAD-3
- Optional built-in strobe synchronization
 - Supports coded audible signals including Temporal 3 pattern
- Battery supervision and control
- Packaged in self-contained, sheet-metal enclosure
 - Easily capable to house the required
- 7AH back-up battery set
- Multi-module mounting in System 3TM enclosures
- Multiple modules share battery set
- Americans with Disabilities Act (ADA) Compliant
- UL 864 10th Edition Listed, ULC S527-11 Listed
- FM, CSFM & NYC Fire Department Approved

Product Overview

Used with Siemens Fire Safety fire alarm control panels (FACPs), the Distributed Power Supply Unit (Model PAD-3 series) is a NAC expander with a built-in, auxiliary-power output. Each unit is designed to provide additional power for visual indicators in buildings that conform to the Americans with Disabilities Act (ADA).

Each Model PAD-3-series unit provides the following physical characteristics:

- NACs
- Unit enclosure
- Signal-input circuits
- Battery-charging circuit
- Trouble relays for remote monitoring
- Diagnostic light-emitting diodes (LEDs)
- Alternating Current (AC) power connection


The Siemens NACs, which connect with alarm signaling devices, have been designed to provide the highest level of reliability and performance.

Specifications

Each unit provides 6A @ 24VDC power for multiple uses, and all 6 Amps can be directed to four (4) NACs. Each NAC is power limited; rated at 3A. Either one (1) or two (2) inputs can control the four (4) outputs. These outputs are compatible with all Siemens Fire Safety 24VDC notification appliances.

In order to makes the outputs easily programmable, this version of the Siemens Auxiliary Power Supply (Model PAD-3) can be configured in the following manner:

- 'STEADY' outputs
- Synchronized strobe outputs
- American National Standards Institute (ANSI) Temporal 3



Model PAD-3-MB
Main Board



Model EN-PAD
Black Enclosure for
PAD-3 unit



Specifications (cont.)

Each PAD-3 NAC extender unit can be configured in a way that each input circuit can be programmed as steady output, ANSI temporal output, or synchronized strobe output. Also, programming can be set so one (1) input will silence the audible signal on Siemens Models AS-series, NS-series, or ZH-series horn and horn-strobes while the strobes remain active.

Model PAD-3 is capable of operating other components within a Siemens fire alarm system, such as door holders, via 3 Amps @ 24VDC max of power-limited auxiliary output. When using this output, the total power available from the NAC extender unit cannot exceed 6 Amps.

A 'Form C' dry contact is provided for monitoring *Trouble* conditions through each input. In addition, a 'Form C' *Trouble* contact is provided for monitoring Model PAD-3 connected through the input of a Siemens FACP. The user, therefore, has the option of connecting Model PAD-3 to a notification circuit of a Siemens FACP, or monitoring Model PAD-3 with a Model TRI-series monitoring module on a Siemens Intelligent Fire System.

Model PAD-3 supervises a variety of functions including:

- Low AC power
- Battery-voltage level
- Earth ground-fault conditions
- Auxiliary output power-limited conditions
- End-of-Line (EOL) supervision *Trouble condition*, or power-limited condition at an output

Model PAD-3 provides 6A at 24 VDC power, directed to two (2) 'Class A' or four (4) 'Class B' power-limited NACs. Each NAC supports up to 3 Amps per circuit. Either one (1) or two (2) inputs can control four (4) outputs, which are compatible with all Siemens Fire Safety 24VDC alarm signaling devices. System 3 enclosures may also be used to house multiple Model PAD-3 units in a single enclosure, via the Model S3AP Adapter Plate. Two (2) units are capable of sharing the same battery set when mounted in the same enclosure.

Each Model PAD-3 unit complies with seismic certification, pursuant to the following:

- ASCE Standard 7, 2005 Edition
- International Building Code, 2006 Edition
- California Building Code, 2007 Edition
- ICC-ES AC 156, effective 2007
- OSHPD preapproved, under: OSP-0057-10
- OSHPD CAN 2-1708A.5, Rev. 3

The Model PAD-3 battery charger can charge up to 15AH batteries. Each unit is packaged in its own sheet-metal enclosure with sufficient space to house up to 7AH battery sets. PAD-3 enclosures are available in either **Black** or **Red**. When battery sets greater than 7AH are required, the battery set must be housed in a System 3 enclosure or a separate UL / ULC Listed battery enclosure.

System 3 enclosures may also be used to house multiple Model PAD-3 units in a single enclosure, via the Model S3AP Adapter Plate. Two (2) units are capable of sharing the same battery set when mounted in the same enclosure.

Each Model PAD-3 unit complies with seismic certification, pursuant to the following:

- ASCE Standard 7, 2005 Edition
- International Building Code, 2006 Edition
- California Building Code, 2007 Edition
- ICC-ES AC 156, effective 2007
- OSHPD preapproved, under: OSP-0057-10
 - OSHPD CAN 2-1708A.5, Rev. 3

LED Indicators	
COLOR	CONDITION
GREEN:	AC Power ON
YELLOW:	Battery <i>Trouble</i>
YELLOW:	Ground Fault
YELLOW:	Auxiliary <i>Trouble</i>
YELLOW:	Output 1 <i>Trouble</i>
YELLOW:	Output 2 <i>Trouble</i>

Temperature and Humidity Range

Model PAD-3 is UL 864 10th Edition Listed for indoor dry locations within a temperature range of 120+/-3°F (49+/-2°C) to 32+/-3°F (0+/-2°C) and a relative humidity of 93+/-2% at a temperature of 90+/-3°F (32+/-2°C)

Technical Data

Trouble Contact Rating: 'Form C'	2.5A @ 250VAC, 30VDC
AC Input	2.5A @ 120VDC
Input Configurations:	Two (2) 'Class B' or Two (2) 'Class A'
Input Current:	0.006A, max.
Input Voltage Range:	9 – 32VDC
Auxiliary Power Circuit:	One (1) circuit @ 3A max.
Battery Charging Capacity:	15AH
Notification Circuits:	Four (4) circuits
Ambient Temperature:	32° – 120° F (0° – 49° C)
Relative Humidity:	Up to 93% @ 86° F (30° C) non-condensing
NAC Outputs:	24VDC @ 3.0A each
	24K ohm EOL resistor required on each 'Class B' circuit
Amps per Output Circuit:	3.0
Total Output:	24VDC @ 6 Amps (with Model FP2016-U1)
Output Configurations:	Two (2) 'Class A'
	Four (4) 'Class B'
	One (1) 'Class A'
	Two (2) 'Class B'

Configuration Options

Option	Input[s]	Output Controls	Circuit Types
1	Input 1	All outputs	'Class B' circuits
2	Input 1	All outputs	'Class B' circuits
	Input 2*	Silences horns on Output 1	—
3	Input 1	Outputs 1 and 2	'Class B' circuits
	Input 2	Outputs 3 and 4	
4	Input 1	Output 1	'Class B' circuits
	Input 2	Outputs 2, 3 and 4	
5	Input 1	Outputs 1 through 4	'Class A' circuit pairs
6	Input 1	Outputs 1 through 4	'Class A' circuit pairs
	Input 2*	Silences horns on Output 1	
7	Input 1	Outputs 1 and 2	'Class A' circuit pairs
	Input 2	Outputs 3 and 4	

*denotes when used with Siemens Model AS, NS or ZH-Series horn / strobe NAC Devices

Details for Ordering

MODEL OR TYPE	PART NUMBER	PRODUCT
PAD-3	599-699189	NAC Extender with Black enclosure (Up to 6A Pwr. Supply)
PAD-3R	599-699190	NAC Extender with Red enclosure (Up to 6A Pwr. Supply)
PAD-3-MB	500-699080	Main board used for Model PAD-3 Series
EN-PAD	310-099073	Black enclosure for PAD-3 unit
EN-PADR	310-099150	Red enclosure for PAD-3 unit

Optional Accessory

MODEL OR TYPE	PART NUMBER	PRODUCT
PAD-3-UK	500-648449	Battery brackets PAD-3-UK Upgrade Kit

Note: The Distributed Power Supply Unit is referred as Model **PAD-3C** in **Canada**.

Physical Properties

PAD-3 Enclosure	
Single-Unit Dimension: (W-x-H-x-D)	12.2" —x— 16.4" —x— 3.1" (31 cm. -x- 41.7 cm. -x- 7.9 cm.)
Colors:	Black or Red

This Page Left Intentionally Blank

NOTICE – The information contained in this data-sheet document is intended only as a summary, and is subject to change without notice. The product(s) described here has/have a specific instruction sheet(s) that cover various technical, limitation and liability information.

Copies of install-type, instruction sheets – as well as the *General Product Warning and Limitations* document, which also contains important data, are provided with the product, and are available from the Manufacturer.

Data contained in the aforesaid type of documentation should be consulted with a fire-safety professional before specifying or using the product.

Any further questions or assistance concerning particular problems that might arise, relative to the proper functioning of the equipment, please contact the Manufacturer.

SIEMENS

Siemens Industry, Inc.
Smart Infrastructure - Building Products
2 Gatehall Drive • Parsippany, NJ 07054
Tel: (973) 593-2600

February - 2023
(Rev. 2)