


DC POWER SUPPLY: 24 VAC TO 1.5 - 14 VDC

PSM20A12DAS

DC Power Supply, Isolated Linear, 24 Vac to 1.5Vdc-14Vdc, 300mA Adjustable Output, Track Mount



SPECIFICATIONS

<p>Voltage Input: 24 Vac Voltage Output: 1.5 - 14 Vdc Isolated Frequency: 50/60 Hz Overload Protection: Electrical and Thermal, Auto-Reset Operating Temperature: -30 to 140° F Humidity Range: 5 to 95% (noncondensing) Power Status: LED On = Activated Dimensions: 2.75"H x 4.00"W x 1.75"D1/2.25"D2 Housing Detail: See Housing H in housing guide for dimensions Origin: Made of US and non-US parts Track Mount: 4.000" and 2.750" MT212-4 Mounting Track Supplied ON/OFF Switch: 2 Position Approvals: Class 2, UL916, C-UL, CE, RoHS,</p>	<p>Output Current Ratings: 300 mA @ 12 Vdc</p> <p>Input Current Rating: 950 mA Maximum</p>	<p>Percent Ripple: 0.0016%, 12 Vdc @ 300 mA</p> <p>Regulation: Load: 0.04% No Load to Full Load Line: 0.0080 mV/V</p>
--	--	---