

Functional Devices, Inc. | 101 Commerce Drive, Sharpsville, IN 46068

Email: sales@functionaldevices.com | Website: www.functionaldevices.com Toll Free: (800) 888-5538 | Office: (765) 883-5538 | Fax: (765) 883-7505


AC POWER SUPPLIES: 120 VAC TO 24 VAC

PSMN40A

40 VA Power Supply, 120 Vac to 24 Vac, 2.75" Track Mount

PSMN40AS

40 VA Power Supply, 120 Vac to 24 Vac, Switch, 2.75" Track Mount















SPECIFICATIONS

Transformers: One 40 VA
Primary: 120 Vac
Secondary: 24 Vac, isolated
Frequency: 50/60 Hz
and Protection: Inherently limited

Overload Protection: Inherently limited
Operating Temperature: -30 to 140° F
Humidity Range: 5 to 95% (noncondensing)

Power Status: LED On = Secondary Voltage Present
Dimensions: 3.25" H x 2.75" W x 2.00" D1/2.50" D2
Housing Detail: See Housing H in housing guide for dimensions

Track Mount: MT212-4 Mounting Track Supplied

ON/OFF Switch: 2 Position (PSMN40AS)

Max. Ambient Temperature: 40° C

Approvals: UL916, UL508, C-UL, CE, RoHS Origin: Made of US and non-US parts