



**30 AMP TRACK MOUNT CONTROL RELAY**

**RIBM013PN**

Power Relay, 30 Amp 3PDT, 120 Vac Coil, 4.00" Track Mount



**SPECIFICATIONS**

- # Relays & Contact Type: One (1) 3PDT Continuous Duty Coil
- Expected Relay Life: 10 million cycles minimum mechanical
- Operating Temperature: -30 to 140° F
- Humidity Range: 5 to 95% (noncondensing)
- Operate Time: 20ms
- Relay Status: LED On = Activated
- Dimensions: 2.38"H x 4.00"W x 1.38"D1/1.88"D2
- Housing Detail: See **Housing H** in housing guide for dimensions
- Track Mount: 4.000"  
MT4 Mounting Track Sold Separately
- Origin: Made of US and non-US parts
- Approvals: UL Component Recognized, UL916, UL864  
 C-UL, California State Fire Marshal, CE, RoHS
- Gold Flash: No
- Override Switch: No

**Contact Ratings:**

- 30 Amp General Use @ 300 Vac
- 30 Amp Resistive @ 28 Vdc
- 20 Amp Ballast @ 277-480 Vac
- Not rated for Electronic Ballast
- 15 Amp Resistive @ 600 Vac
- 7.5 HP @ 480 Vac, 3 Phase
- 5 HP @ 240 Vac, 3 Phase
- 3 HP @ 480-600 Vac, 1 Phase
- 2 HP @ 240-277 Vac, 1 Phase
- 1 HP @ 120 Vac, 1 Phase

- Heavy Pilot Duty @ 600 Vac
- 770 VA @ 120 Vac, 1 Phase
- 1,158 VA @ 240 Vac, 1 Phase
- 1,110 VA @ 277 Vac, 1 Phase
- 1,640 VA @ 480 Vac, 1 Phase
- 1,466 VA @ 240 Vac, 3 Phase
- 2,122 VA @ 480 Vac, 3 Phase

**Coil Current:**

140 mA @ 120 Vac

**Coil Voltage Input:**

120 Vac ; 50-60 Hz  
 Drop Out = 35 Vac  
 Pull In = 85 Vac