

WIRELESS OCCUPANCY / VACANCY SENSOR

WVSWM-EN3

EnOcean 902 MHz Wireless Vacancy / Occupancy Sensor, Wall Mount

SPECIFICATIONS

RF Transmission Range: 80 ft.
Motion Sensing Range: Up to 100 ft. (refer to coverage diagrams)

Startup Charge Times

First Motion Transmission / Linking: 5 minutes at 200 lux
Motion LED Blink Light / Walk Test Modes: 1.5 hours at 2000 lux
Sustaining Charge Time: 3 hours per 24 hours at 200 lux
Time to Full Charge: 25 hours at 200 lux

Operating Life in Total Darkness: 80 hours (after full charge)
Minimum Operating Light: 50 lux (for auto-off only)

Motion Transmission Interval: 2 minutes
Unoccupied Transmission: 10 and 30 minutes since last motion

Dimensions: 5.83" L x 2.52" W x 1.8" D (148 mm x 64 mm x 45.7 mm)

Mounting Height: 6-8 feet recommended

Environment: Indoor use only
14° to 104° F (-10° to 40° C)
20 to 95% relative humidity (noncondensing)

Approvals: RoHS, R&TTE

Agency Compliance: FCC ID: SZV-STM300U
IC: 5713A-STM300U



Notes:

- Only for use with -EN3 Series relays.
- EEP A5-07-01