


IP-5IRD4C4A5-28

4MP Full-Color Turret Network Camera



- H.265+ / H.265 / H.264 +/H.264 / MJPEG coding
- Max. resolution: 2688 × 1520
- 20~30m white light view distance
- 24/7 full color imaging
- 3D DNR, WDR, HLC, BLC, and ROI coding
- Support electronic image stabilization
- Support image distortion correction
- Support 1CH audio input; 1 CH built-in MIC
- Built-in micro SD card slot; up to 512GB
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- Multiple smart events can be enabled at the same time
- Support P2P function
- Support dual-system backup



TITANIUM IP-5IRD4C4A5-28


4MP Full-Color Turret
Network Camera

SPECIFICATIONS

Model	IP-5IRD4C4A5-28			
Specifications				
Camera				
Image Sensor	1 / 1.79 "CMOS			
Image Size	2688 × 1520			
Electronic Shutter	Auto or manual mode; manual mode: 1 / 3s ~ 1 / 100000 s			
Iris Type	Fixed Iris			
Min. Illumination	0.0001 lux @F1.0, AGC ON; 0 lux with illumination on			
S/N Ratio	≥50dB			
Lens	2.8 mm@F1.0, H.FoV: 112°; V.FoV:61°; D.FoV:132° 3.6 mm@F1.0, H.FoV: 96°; V.FoV: 51°; D.FoV:112°			
Focus	Fixed			
Lens Mount	M12			
Wide Dynamic Range	120dB (the next version will support)			
BLC	Yes			
HLC	Yes			
Defog	Yes			
Digital NR	3D DNR			
EIS	Yes			
Angle Adjustment	Pan: 0°~360°; Tilt:0°~80°; Rotation: 0°~360°			
Image				
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream/Third stream: H.265+ / H.265 / H.264+ / H.264/ MJPEG			
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile			
Resolution	4MP (2688×1520),2K (2560×1440), 1080P (1920×1080), 720P (1280×720), D1, VGA (640 ×480), 640 ×360, CIF, 480×240			
Main Stream	4MP/2K/1080P(60Hz : 1 ~ 30fps; 50Hz: 1~25fps)			
Sub Stream	720P/D1/640 ×360/VGA/CIF/480×240 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)			
Third Stream	720P/D1/640 ×360/VGA/CIF/480×240 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)			
Bit Rate	32 Kbps ~8 Mbps			
Bit Rate Type	VBR / CBR			
Audio Compression	G711A / U			
Image Settings	ROI, Saturation, Brightness, Hue, Contrast,Wide Dynamic, Sharpness, Image Flip, Image Mirror, NR, etc. adjustable through client software or web browser			
ROI	Each ROI to be configured separately			
Interfaces				
Network	RJ 45 (10/100 Base-T)			
Video Output	No			
Audio	1CH audio input; 1CH built-in microphone			
Storage	Built-in micro SD card slot; up to 512GB			
Reset	Yes			
Alarm	No			
Intelligent Analytics				
Smart Event	Line crossing, region intrusion/entrance/exiting (human/vehicle classification), abandoned/ missing object detection			
Statistics	Target counting by line (human/vehicle classification)			
Exception Detection	Scene change, video blur and abnormal color detection, audio exception			
Face Detection	Face detection, face capture			
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8mm	52m(170ft)	21m(68ft)	10m(33ft)	5m(17ft)
3.6mm	63m(207ft)	25m(82ft)	12m(40ft)	6m(20ft)
Functions				
Remote Monitoring	Web Client/Titanium NVR/NVMS/mobile APP			
Web Browser	Chrome 92.0+/Edge 92.0+/Firefox 91.0+/Safari 13.1+			
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission			
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, FTP, PPPoE, DDNS, SMTP, SNMP, HTTP, 802.1x, UPnP, HTTPS, HTTP POST, P2P, QoS			

Interface Protocol	ONVIF
API & SDK	Yes
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, Network disconnection
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern, ANR, cloud upgrade, disarming
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and token authentication for HTTP/RTSP
PoE	Yes , IEEE802.3af
White Light Range	20 ~30 m
Ingress Protection	IP 67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 6.5W
Storage Conditions	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Ø 111.6 × 99.6
Weight (net)	Approx. 0.616KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS




AVAILABLE MODEL

Available Model	IP-5IRD4C4A5-28
-----------------	-----------------

AVAILABLE ACCESSORIES



NJB130



B9-W



BRACKET11-W