

Auto Fire Extinguisher – Auto FX5 II

Part number 21006287MTL

Regular use

Disposable

UL Rated 5-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Auto unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough aluminum valve assembly.

Includes plastic strap bracket (322057).



At a Glance

- Model Auto FX5 II
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant steel handle
- 6 year limited warranty
- UL approved strap retention bracket

For use on the following types of fire:



P/N: 21006287MTL - 4 pack
 UPC: 0-47871-27013-2
 IZF: 20047871270136

P/N: 21006642MTL - 6 pack
 UPC: 0-47871-27013-2
 IZF: 100478710270139

Product Specification

Net agent weight (Average)	2 lb
Unit weight (Average)	3.2 lb
Diameter	3.25 inches
Height	11.3 inches
Discharge time	8-12 seconds
Discharge range	4-6 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Aluminum and steel

Packaging Options



Packaging dimensions (inches)

	Depth	Width	Height
Carton	3.37	4.25	11.25
Pack (4)	9.1	11.75	7
Pack (6)	9.1	11.75	10



1016 Corporate Park Drive, Mebane, NC 27302 (800) 880-6788 www.Kidde.com

This information is subject to change without notice. Kidde Fire Safety disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Kidde Fire Safety or your local distributor for assistance.