

Kitchen/Garage Fire Extinguisher – FX10K

Part number 466141MTL

Regular use

Disposable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Kitchen/Garage unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough aluminum valve assembly.



Includes plastic strap bracket (322057)

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant steel handle
- 2.9 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (USCG) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection

For use on the following types of fire:



At a Glance

- Model FX10K
- Regular Dry Chemical
- UL listed
- UL rated 10-B:C
- USCG, DOT approved
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires



P/N: 466141MTL - 6 pack
 UPC: 0-47871-27001-9
 IZF - 10047871270016

Product Specification

Net agent weight (Average)	2.9 lb.
Unit weight (Average)	4.0 lb.
Diameter	3.25 inches
Height	14.2 inches
Discharge time	8-12 seconds
Discharge range	6-8 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Aluminum and steel
Strap Bracket	USCG approved

Packaging Options



MASTER PACK

Packaging dimensions (inches)

	Depth	Width	Height
Carton	3.25	4.25	14.1
Master Pack	9.1	14.75	10.0



1016 Corporate Park Drive, Mebane, NC 27302

(800) 880-6788

www.Kidde.com

This information is subject to change without notice. Kidde Fire Safety disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Kidde Fire Safety or your local distributor for assistance.