

Bells Vibrating 55 Series

Edwards 55 Series single magnet vibrating bells feature an exposed striker with an enclosed grounded terminal and case. They are ideal for light duty installations in factory and office environments and OEM applications. They are also suitable for AC powered security systems with a battery standby.

Features and Specifications

- Gray finish
- Low current drain permits long wire runs
- 4" and 6" gong sizes



Ordering Information

| Description | Cat. No. | Operating Voltage | Current | VA | Gong Size | dB at 1m/10ft. | DC Coil Res (Ohms) |
|-------------|----------|-------------------|---------|-----|------------|----------------|--------------------|
| AC | 55-4G5 | 24V AC | 0.20 A | 4.8 | 4" (102mm) | 78/68 | 20.0 |
| | 55-6G5 | 24V AC | 0.20 A | 4.8 | 6" (152mm) | 84/74 | 24.0 |
| AC/DC | 55-4AM | 6V DC | 0.85 A | 5.1 | 4" (102mm) | 78/68 | 2.2 |
| | | 8V AC | 1.10 A | 8.8 | | | |
| | 55-6AM | 6V DC | 0.80 A | 4.8 | 6" (152mm) | 84/74 | 1.9 |
| | | 8V AC | 1.00 A | 8.0 | | | |

Weights and Dimensions

| Cat. No. | Approx. Net Weight (lb.) | Approx. Shipping Weight (lb.) | Dimensions | | |
|----------|--------------------------|-------------------------------|------------|---------------|-----------------|
| | | | A | B | C |
| 55-4AM | 0.96 | 1.08 | 4" (102mm) | 2 1/8" (54mm) | 7 3/8" (187mm) |
| 55-4G5 | 0.96 | 1.08 | 4" (102mm) | 2 1/8" (54mm) | 7 3/8" (187mm) |
| 55-6AM | 1.13 | 2.50 | 6" (152mm) | 2 5/8" (67mm) | 10 5/8" (270mm) |
| 55-6G5 | 1.13 | 2.50 | 6" (152mm) | 2 5/8" (67mm) | 10 5/8" (270mm) |

