

Electronic Audible Signals

Paging Devices

Millennium Class

5542RPU Remote Paging Unit

Sends audio page to, and is powered by the 5540MP-24Y6. Input is received from a microphone input or audio pair signal source such as phone PBX. Indoor, Type 2 enclosure when flush wall mounted. Indoor, Type 12 or 2 when mounted to outdoor listed 4" square utility box. Outdoor, Type 3R and Indoor Type 12 or 2 when mounted with 5542WPK to outdoor listed 4" square utility box.

5542RPU-M Remote Paging Unit

Same as 5542RPU but includes 5542MIC-H Hand Held Microphone.

5542MIC-H Hand Held Microphone

Optional. May be plugged into 5542 RPU either permanently or as needed.

5542MIC-D Desktop Microphone

Optional. May be plugged into 5542RPU either permanently or as needed.

5542WPK Mounting Kit Optional. Intended for use with 5542RPU or 5542RPU-M to provide Type 3R outdoor protection for the 5542RPU series.


Mounting kit for use with the 5542 Series Remote Paging Unit. The mounting kit is UL Listed, CSA Certified and has a Type 3R rating when mounted to the box (included).

MR-201/C Relay

Optional. Used to enable the audio output from the 5540MP-24Y6 to override output from other sources to the same 5532B or 5532BHV series, 5532M or 5532MHV series, 5536M or 5536MHV series, and 5545B series products in the system.

Features and Specifications

- Suitable for outdoor applications when mounted with 5542WPK
- Optional Desk Microphone
- Removeable Microphones
- UL 464 and cUL C22.2 listed No. 205
- NEMA Type 3R



Ordering Information

Description	Cat. No.
Remote Paging Unit	5542RPU
Remote Paging Unit	5542RPU-M

Accessories

Description	Cat. No.
Hand Held Microphone	5542MIC-H
Desktop Microphone	5542MIC-D
Mounting Kit	5542WPK
Relay	MR-201/C



Electronic Audible Signals

Paging Devices

Millennium Class

Weights and Dimensions		
Cat. No.	Approx. Net Weight (lb.)	Approx. Shipping Weight (lb.)
5542RPU	0.50	0.70
5542RPU-M	1.31	1.88
5542MIC-H	0.81	1.18
5542MIC-D	1.75	2.31
5542WPK	0.42	0.70
MR-201/C	0.50	0.85

5542RPU with 5542WPK Mounting Kit (suitable for outdoor applications)

