

Electronic Audible Signals

Speaker Amp

Titan Class

The 5545M Hazardous Location Remote Speaker/ Amplifier has been designed for high decibel system operation when connected to the 5540M Central Tone Generator or 5541M System Master Panel.

Features and Specifications

- Corrosion resistant electrostatic heat flowed epoxy finish
- Individual volume control
- Speaker swivels 180° vertically or horizontally depending on orientation of mounting bracket
- 30" (762mm) numbered wire leads
- Supplied with factory sealed 1/2" (13mm) threaded fitting for quick installation
- Heavy duty zinc cast construction
- 100dB @ 1m (90dB @ 10ft.)
- UL listed for Class 1, Div. 1 and 2, Groups B, C and D hazardous locations



Ordering Information				
Description	Cat. No.	Operating Voltage ¹	Typical Current	
			Standby	Tone On
High Decibel, Explosionproof	5545M-AQ	24V DC	0.061 A	0.47 A
		24V AC	0.25 A	0.95 A
	5545M-Y6	120-240V AC	0.10 A	0.28-0.15 A
		125-250V DC	0.11-0.02 A	0.15-0.08 A
	5545M-25Y6	120-240V AC	0.10 A	0.28-0.15 A
		125-250V DC	0.11-0.02 A	0.15-0.08 A
	5545M-70Y6	120-240V AC	0.10 A	0.28-0.15 A
		125-250V DC	0.11-0.02 A	0.15-0.08 A

¹AC voltage frequency is 50/60 Hz.

Weights and Dimensions		
Cat. No.	Approx. Net Weight (lb.)	Approx. Shipping Weight (lb.)
5545M-AQ	16.50	23.50
5545M-Y6	16.50	23.50
5545M-25Y6	16.50	23.50
5545M-70Y6	16.50	23.50

